

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION RECEIVED

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

APR 18 1980

O. C. D.
ARTESIA OFFICE

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO REDEVELOP OR REEQUIP AN EXISTING WELL IN A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT TO DRILL" (FORM C-101) FOR SUCH PROPOSALS.)

1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER _____

2. Name of Operator
Yates Petroleum Corporation

3. Address of Operator
207 South 4th Street-Artesia, NM 88210

4. Location of Well
UNIT LETTER M 330 FEET FROM THE South LINE AND 990 FEET FROM
THE West LINE, SECTION 31 TOWNSHIP 18S RANGE 25E NMPLAS

15. Elevation (Show whether DF, RT, GR, etc.)
3652'

5a. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.
L-122

7. Unit Agreement Name

8. Form or Lease Name
Penasco "IW" (Shallow)

9. Well No.
1 2

10. Field and Pool, or Wildcat
Penasco Draw SA Yeso (Assoc)

12. County
Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☐	Set Prod csg, perf and treat ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 3150' - Ran 77 joints of 4½" 9.5# J-55 (3122') of casing set at 3122'.
1-Diff-fill shoe at 3122'. Cemented by Dowell w/350 sacks Class C 2/10%
D-65, 3/10 gal/sack D-108. PD 1:29 PM 3-25-80. Circulated 10 sacks of
cement to pit.

TD 3150'; PBTD 3122' - WIH w/Steel Strip Carrier gun and perforated 2454-2854'
w/29 .50" holes (1 shot at each depth) as follows: 2454', 2457, 2462, 2465½,
2504, 2507, 2522, 2548, 2551, 2556, 2574, 2609½, 2613, 2615½, 2619, 2621½,
2669, 2671, 2675, 2680, 2684, 2778, 2793, 2800, 2803, 2841, 2846½, 2852 &
2854'. Sand Frac'd perforations w/3000 gallons 15% DS-30 acid, 60000 gallons
gelled treated water and 95000# of sand, 75000# 20-40 sand and 20000# mesh.
Prep to install pumping equipment.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christine Tomlinson TITLE Geol. Secty. DATE 4-18-80

APPROVED BY W. A. Grasset TITLE SUPERVISOR, DISTRICT II DATE APR 21 1980

CONDITIONS OF APPROVAL, IF ANY: