

Form 9-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 11326

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Rio Pecos "NF" Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undesignated

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREAUnit C
Sec. 33, T18S, R27E

NMPM

1. ☐ OIL
WELL ☐ GAS
WELL ☐ OTHER Dry Hole

JUN 2 1980

2. NAME OF OPERATOR

Yates Petroleum Corporation

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

3. ADDRESS OF OPERATOR

207 South 4th Street, Artesia, New Mexico 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)
At surface

660' FNL & 1980' FWL Sec. 33, T18S, R27E, NMPM JUL 24 1980

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3379' GR

O. C. D.
ARTESIA, OFFICE

12. COUNTY OR PARISH

Eddy

13. STATE

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 7 7/8" hole to TD of 1850. Propose to plug and abandon as follows:

GIH with tubing and displace hole with heavy mud.

Spot cement plug through tubing from 1156' - 1255' (35 sx)

Spot cement plug through tubing from 696' - 796' (35 sx)

Spot cement plug through tubing across 8 5/8" casing shoe from 331' - 431' (35 sx)

Spot 15 sack cement plug at surface and install regulation abandonment marker.

Restore location as required.

25

18. I hereby certify that the foregoing is true and correct

SIGNED

Albert R. Hall

TITLE

Engineer

DATE

May 26, 1980

(This space for Federal or State office use)

APPROVED BY

PETER W. CHESTER

TITLE

ACTING DISTRICT ENGINEER

DATE

JUL 23 1980

CONDITIONS OF APPROVAL, IF ANY: