

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Gabe Reth Corp.</u>		Lease <u>Penasco 1W Shallow</u>		Well # <u>3</u>	
Location of Well	Unit <u>3305 230W</u>	Section <u>31</u>	Township <u>18</u>	Range <u>25</u>	County <u>Eddy</u>
Drilling Contractor <u>Castro & Co.</u>			Type of Equipment <u>Rotary</u>		

APPROVED CASING PROGRAM

* Witness					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
15"	10 3/4"	32.75		320	275 circ.
9 7/8"	7"	20		1000	500 "
6 1/4"	4 1/2"	9.5		3100	200 "

Casing Data:

Surface joints of 7 inch 20 # Grade J-SS
(Approved) (Rejected)
Inspected by M.S. date 4/16/80

Cementing Program

Size of hole 9 1/2" Size of Casing 7" Sacks cement required
Type of Shoe used guide Float collar used insert Btm 3 jts welded yes
TD of hole 1019' Set 1018' Feet of 7 Inch 20 # Grade J-SS
New-used csg. @ 1018' with 15029 cc sacks neat cement around shoe
+ 100 sax C 370 cc additives
Plug down @ 3:00 (AM) (PM) Date 4/17/80
Cement circulated No No. of Sacks -0-
Cemented by Dowell Witnessed by Mike Stuppfield
Temp. Survey ran @ 8:00 (AM) (PM) Date 4/17/80 top cement @ 400'
Casing test @ (AM) (PM) Date
Method Used Witnessed by
Checked for shut off @ (AM) (PM) Date
Method used Witnessed by
Remarks: + 450 6 5/35 puz. (4 D²⁰, 8# Kolite, 1/4# celoflakes, 370 cc)

No centralizers
lost circ. @ 585'
lost drill break @ 918'

1. Ran 1" Tagged TOC @ 382'
Pumped 170 sx C.
Cement circulated.