

DISTRIBUTION		
ART A FE	1	
FILE	1	✓
U.S.G.S.		
LAND OFFICE		
OPERATOR	1	

N MEXICO OIL CONSERVATION COMMISSIO

Supersedes Old
C-102 and C-103
Effective 1-1-65

RECEIVED

MAY - 5 1980

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

ARTESIA, OFFICE

Name of Operator

Yates Petroleum Corporation

Address of Operator

207 South 4th Street-Artesia, NM 88210

Location of Well

UNIT LETTER N 330 FEET FROM THE South LINE AND 2310 FEET FROM

THE West LINE, SECTION 31 TOWNSHIP 18S RANGE 25E NMPH.

15. Elevation (Show whether DF, RT, GR, etc.)

3643' GR

5a. Indicate Type of Lease

State ☒ Fee ☐

5. State Oil & Gas Lease No.

L-122

7. Unit Agreement None

8. Farm or Lease Name

Penasco "IW" Shallow

9. Well No.

1 3

10. Field and Pool or Valued

Penasco Draw SA Yeso (Assoc)

12. County

Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

REMEDIAL WORK ☐

ALTERING CASING ☐

TEMPORARILY ABANDON ☐

COMMENCE DRILLING OPS. ☒

PLUG AND ABANDONMENT ☐

WELL OR ALTER CASING ☐

CHANGE PLANS ☐

CASING TEST AND CEMENT JOB ☒

OTHER ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 14-3/4" hole at 11:45 PM 4-14-80. TD 360' - Ran 9 jts of 10-3/4" 30# J-55 (361') of casing set at 360'. 1-Guide shoe at 360' and insert float at 320'. Cmt'd w/350 sx Class C 4% CaCl. PD 2:15 PM 4-15-80. Cmt circ. 40 sx to surface. WOC 12 hrs, backed off & reduced hole to 9 1/4", drld plug and tstd to 600# OK & resumed drilling.

TD 1018' - Ran 25 jts 7" 20# K-55 ST&C (1018') of casing set at 1018'. 1-guide shoe at 1018' & insert float at 978'. Cmt'd w/100 sx Class C 2% CaCl, 450 sx 65-35, 5#/sx gilsonite, 1/4#/sx celloflakes, followed w/150 sx Class c 2% CaCl. PD 3:00 AM 4-17-80. Cmt did not circ. Ran Temp. Survey & found top of cmt at 400'. Ran 1" & tagged cmt at 398', sptd 170 sx Class C 4% CaCl. PD 9:00 AM 4-17-80. Circulated 10 sx of cmt to surface. WOC 18 hrs, NU, reduced hole to 6 1/4" tstd to 600# after drilling plug OK and resumed drilling.

TD 3145'; PSTD 3130' - Ran 72 jts of 4 1/2" 9.5# K-55 (3132') of csg set at 3130'. 1-guide shoe at 3130'. Cmt'd w/350 sx Class C 3/10% CFR-2, 2/10% Halad-9. PD 5:00 PM 4-25-80. Cmt circ. 5 sx to surface.

Perforated 2673-91' w/10 .50" holes, broke formation down w/500 gals 15% acid. Sand Frac'd w/2000g 15% reg. acid, 39868 gal trtd KCLwtr & 55000# sand, 15000# 100 mesh and 40000# 20-40 sand.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

WELDED

Geol. Secty.

DATE 5-3-80

APPROVED BY

TITLE

SUPERVISOR, DISTRICT II

DATE

MAY - 6 1980

CONDITIONS OF APPROVAL, IF ANY