

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

JUN 10 1980

O. C. D.

ARTESIA, OFFICE

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. L-4496
7. Unit Agreement Name
8. Farm or Lease Name Southland "NP" State
9. Well No. 1
10. Field and Pool, or Wildcat Penasco Draw SA Yeso (Assoc)
12. County Eddy

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- 2. Name of Operator Yates Petroleum Corporation ✓ 3. Address of Operator 207 South 4th Street - Artesia, NM 88210 4. Location of Well UNIT LETTER <u>O</u> <u>330</u> FEET FROM THE <u>South</u> LINE AND <u>1650</u> FEET FROM THE <u>East</u> LINE, SECTION <u>31</u> TOWNSHIP <u>18S</u> RANGE <u>25E</u> NMPM. 15. Elevation (Show whether DF, RT, GR, etc.) 3620'	7. Unit Agreement Name 8. Farm or Lease Name Southland "NP" State 9. Well No. 1 10. Field and Pool, or Wildcat Penasco Draw SA Yeso (Assoc) 12. County Eddy
---	--

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	
		OTHER <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 14-3/4" hole at 12:00 AM 5-30-80.

TD 306' - Ran 8 joints of 10-3/4" 40.5# ST&C (307') of casing set at 306'.
1-Texas Pattern guide shoe at 306'. 1-Insert float at 268'. Cemented w/350
sacks Class C 4% CaCl. PD 4:00 PM 5-30-80. Circulated 40 sacks of cement
to the surface. WOC 12 hours, backed off, reduced hole to 9 1/2", drilled
plug and tested to 600# OK and resumed drilling.

TD 985'- Ran 23 joints of 7" 20# ST&C (987') of casing set at 985'. 1-
Texas Pattern guide shoe at 985' and insert float at 945'. Cemented w/250
sacks Neat Class C, 450 sacks 65-35 Poz, 8# Kolite, 1/4# celloflake and 3%
CaCl. Tailed in w/150 sacks of Class C 2% CaCl. PD 9:30 AM 6-1-80. Circulate
20 sacks of cement to the surface. NU and tested to 1500# OK, reduced hole
to 6-1/4", drilled plug and tested to 600# OK and resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christine Tomlinson TITLE Geol. Secty. DATE 6-9-80APPROVED BY W.A. Gressett TITLE SUPERVISOR, DISTRICT II DATE JUN 11 1980

CONDITIONS OF APPROVAL, IF ANY: