

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN 1
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE NUMBER AND SERIAL NO.

LC-06348-067348

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

MAY - 8 1980

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	2. NAME OF OPERATOR Yates Petroleum Corporation	3. ADDRESS OF OPERATOR 207 South 4th Street - Artesia, NM 88210	4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' FEL & 1680' FNL of Section 28-18S-29E	5. FIELD AND POOL OR WILDCAT and North Turkey Wildcat Track Morro	6. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 28-18S-29E Unit G NMPM	7. COUNTY OR PARISH Eddy	8. STATE NM
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3440' GR						

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 2878' - Ran 70 joints of 8-5/8" 32# & 24# K-55 ST&C casing as follows: 12 joints of 32# (500'); 41 joints 24# (1684') & 17 joints 32# (700') (Total 2884') of casing set at 2878'. 1-guide shoe at 2878' and insert float at 2837'. Cemented w/1200 sacks Howco Lite, 10#/sack gilsonite, 1/4#/sack flocele, 2% CaCl. Tailed in w/150 sacks of Class C 2% CaCl. PD 11:30 AM 4-26-80. Cement did not circulate. Ran Temperature Survey and found top of cement at 750'. Ran 1", tagged cement at 680', spotted 150 sacks Class C 4% CaCl. PD 6:30 PM 4-26-80. WOC 2 hours. Ran 1", tagged cement at 350', spotted 150 sacks Class C 4% CaCl. PD 9:00 PM 4-26-80. Cement circulated 5 sacks to surface. WOC and cement fell back, filled to surface w/5 yards of Ready-Mix. WOC 18 hours, NU, reduced hole to 7-7/8", drilled plug and tested to 600# OK and resumed drilling.

18. I hereby certify that the foregoing is true and correct

SIGNED

Christine Lombroso

TITLE

Geol. Secty

DATE

5-3-80

(This space for Federal or State office use)

APPROVED BY

(Orig. Sgd.) GEORGE H. STEWART

TITLE

ACTING DISTRICT ENGINEER

DATE

MAY 07 1980

CONDITIONS OF APPROVAL, IF ANY: