

DISTRIBUTION		
SANTA FE	1	
FILE	1	✓
U.S.G.S.		
LAND OFFICE		
OPERATOR	1	

NEW MEXICO OIL CONSERVATION **RECEIVED**

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-85

JUN 27 1980

O. C. D.

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. L-4379

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-	7. Unit Agreement Name
2. Name of Operator MONSANTO COMPANY	8. Form or Lease Name SRC 35 State
3. Address of Operator 1330 Midland NBT, Midland, Tx. 79701	9. Well No. 1
4. Location of Well UNIT LETTER <u>I</u> <u>2310</u> FEET FROM THE <u>South</u> LINE AND <u>330</u> FEET FROM THE <u>East</u> LINE, SECTION <u>35</u> TOWNSHIP <u>18S</u> RANGE <u>27E</u> NMPM.	10. Field and Pool, or Wildcat Artesia Queen(Grayburg-SA)
15. Elevation (Show whether DF, RT, GR, etc.)	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASINGS <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drill 7 7/8" hole to 1997'.

Ran 4 1/2" 10.6# K-55 ST&C casing set at 1997'. Cemented w/ 300 Sks. Class "H" + 5#/Sks. Gilsonite & 1/4#/Sks. CF + 2% Low Dense. Tail in w/ 250 Sks. Class "C" + 2% CaCl. Plug down @ 5 AM. Circ 50 Sks Cement to surface. Tested to 2000 psi for 30 Mins., held Ok.

Release drilling rig.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>[Signature]</u>	TITLE <u>Regional Prod. Mgr.</u>	DATE <u>6/26/80</u>
APPROVED BY <u>[Signature]</u>	TITLE <u>OIL AND GAS INSPECTOR</u>	DATE <u>JUN 30 1980</u>
CONDITIONS OF APPROVAL, IF ANY:		