

UNITED STATES DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

N.M.O.C.D. COPY

SUBMIT IN TRIPLI  
(Other instructions  
verse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-0924

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Sivley Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Loco Hills-Q.G.S.A.

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec 31 18S 29E

12. COUNTY OR PARISH

13. STATE

Eddy

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

SEP 18 1980

O. C. D.

ARTESIA, OFFICE

RECEIVED

SEP 11 1980

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Frostman Oil Corporation

3. ADDRESS OF OPERATOR

P.O. Box 161, Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)

At surface

990 FNL 330 FEL Sec 31-18S-29E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3431 GR

U.S. GEOLOGICAL SURVEY

ARTESIA, NEW MEXICO

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETION

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT\*

(Other) Surface & Oil String

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \*

1. Drilled 12 1/2" hole to 391'. Ran 9 jts 8 5/8" 23# K-55 casing 371' set at 386'. Cemented with 250 sx Class C with 2% CaCl cement. Cement circulated. W.O.C. 18 hours. Pressure tested casing 1000# held okay.
2. Drilled 7 7/8" hole to 3000'. Ran 73 jts 4 1/2" 9.5# 8rd ST & C. Casing 3015 feet set at 3000 feet. Cemented with 875 sx Haliburton light with 8# salt per sack followed by 400 sacks Haliburton 50/50 Pos with 2% gel 8# salt per sack. Plug down 9:30 a.m. 8-9-80.

18. I hereby certify that the foregoing is true and correct

SIGNED

*Clayton Smith*

TITLE

President

DATE

9/8/80

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

\*See Instructions on Reverse Side

DATE
ACCEPTED FOR RECORD
<i>D. Chester</i>
SEP 15 1980
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO