

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐

2. NAME OF OPERATOR  
Amoco Production Company

3. ADDRESS OF OPERATOR  
P. O. Box 68 Hobbs, NM 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 890' FNL & 2245' FWL, Sec. 10  
AT TOP PROD. INTERVAL: (Unit C, NE/4, NW/4)  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPCRT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input checked="" type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) <input type="checkbox"/>	<input type="checkbox"/>

5. LEASE  
NM-025604

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Federal BB

9. WELL NO.  
1

10. FIELD OR WILDCAT NAME

11. SEC. T., R., M. OR BLK. AND SURVEY OR AREA  
10-18-27

12. COUNTY OR PARISH  
Eddy

13. STATE  
NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3510.2 GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

JAN 22 1981

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Moved in a service unit 1-5-81. Tested casing at 600# for 30 min. Tested OK. Perforate 9774' to 9792' with 4 JSPF. Acidized with 2500 gal. 7-1/2% MS Acid with 1000 SCF N/bbl. Swab 2 days and recovered no oil or gas. Ran cast iron bridge plug and set at 9737'. Perforate from 9664' to 9708' with 4 JSPF. Acidize with 7000 gal. 7-1/2% MS acid, additives, and 1000 SCF N/bbl. Currently swab testing.

0+4-USGS, A 1-Hou 1-Susp 1-GLF 1-W. Stafford, Hou  
1-Arco

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Gerald L. Foster TITLE Admin. Analyst DATE 1-20-81

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

ACCEPTED FOR RECORD  
JAN 22 1981  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO