

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.O.S.	
LAND OFFICE	
OPERATOR	1

OIL CONSERVATION DIVISION  
P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

5a. Indicate Type of Lease  
State ☐ Fee ☒  
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DEEPER RESERVOIR.  
USE "APPLICATION FOR PERMIT - II" (FORM C-101) FOR SUCH PROPOSALS.)

RECEIVED

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Amoco Production Company ✓	8. Farm or Lease Name Lutton Com.
3. Address of Operator P. O. Box 68 Hobbs, NM 88240	9. Well No. 1
4. Location of Well UNIT LETTER 0 990 FEET FROM THE South LINE AND 1650 FEET FROM THE East LINE, SECTION 23 TOWNSHIP 18-S RANGE 26-E N.M.P.M.	10. Field and Pool, or Wildcat Und. Atoka Penn
15. Elevation (Show whether DE, RT, GR, etc.) 3304.0 GL	12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled to a TD of 2500' and ran 186' of 32# K-55 8-5/8" casing and 2314' of 24# K-55 8-5/8" casing set at 2500'. Cemented with 1059 SX Lite cement with 5# Gilsonite/SX and 1/2# Flocele/SX and with 350 SX Class C cement with 2% CACL. Circulated 450 SX. Plugged down at 11:15 p.m. 8-15-80. WOC 20 hr. Tested casing with 1500# for 30 min. Test OK. Reduced hole to 7-7/8" and resumed drilling.

0+4-NMOCD, A 1-Hou 1-LBG 1-Suso 1-W. Stafford, Hou

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Bob Davis TITLE Admin. Analyst DATE 8-27-80  
APPROVED BY W.A. Gussitt TITLE SUPERVISOR, DISTRICT II DATE SEP 2 1980  
CONDITIONS OF APPROVAL, IF ANY: