

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen a well back to a different reservoir. Use Form 9-331-C for such proposals.)

RECEIVED

1. oil ☒ gas ☐ other ☐
well well

2. NAME OF OPERATOR

Ray Westall

3. ADDRESS OF OPERATOR

Box 4, Loco Hills, N.M.

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 660FWL 2180FWL, S-27 T18S R-29E

AT TOP PROD. INTERVAL: 1650'

AT TOTAL DEPTH: 3003'

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) Setting Casing

5. LEASE

Denton Federal

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

RECEIVED

8. FARM OR LEASE NAME

Denton Fed. NOV 14 1980

9. WELL NO.

#1

10. FIELD OR WILDCAT NAME

Turkey Track ARTESIA, NEW MEXICO

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

S-27, T-18S, R-29E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3459.3

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

7-24-80 Ran 334' of 24# 3 5/8 casing in 12 1/2" hole. Denton cemented w/250 sx Class C w/4% CaCL. Circulated within 3' of top. Ready mix with 1 yard to surface.

8-1-80 Ran 3003' of 4 1/2" casing 10 1/2#. Cemented with 500 sx of Class C cement.

8-4-80 Perforated San Andres with 4 holes from 2948 to 2954, acidized with 1,000 gal 15% acid. Flowed back and swabbed for 5 hours.

8-6-80 Fraced well at 8bbl minute, 20,000 KCL 2% water, 33,000# sand.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Ray Westall TITLE Operator DATE 11-3-80

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

PETER W. CHESTER

NOV 10 1980

U.S. GEOLOGICAL SURVEY

ROSWELL, NEW MEXICO

See Instructions on Reverse Side