

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Yates Petroleum Corp</u>		Lease <u>Penasco "IW" Shallow</u>		Well # <u>5</u>	
Location of Well	Unit <u>1650S 330E I</u>	Section <u>31</u>	Township <u>18</u>	Range <u>2S</u>	County <u>Eddy</u>
Drilling Contractor <u>Cactus</u>		Type of Equipment <u>Rotary 7-17-80</u>			
* Witness					
<u>APPROVED CASING PROGRAM</u>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>15"</u>	<u>10 3/4"</u>	<u>32.75 #</u>	<u>-</u>	<u>360'</u>	<u>350 SX Circ</u>
<u>9 5/8"</u>	<u>7"</u>	<u>20 #</u>	<u>-</u>	<u>1000'</u>	<u>650 SX Circ</u>
<u>6 1/4"</u>	<u>4 1/2"</u>	<u>9.5 #</u>	<u>-</u>	<u>3100'</u>	<u>375 SX</u>
Casing Data:					
Surface _____ joints of _____ inch _____ # Grade _____ (Approved) (Rejected) _____					
Inspected by _____ date _____					
Cementing Program					
Size of hole <u>9 5/8"</u> Size of Casing <u>7"</u> Sacks cement required _____					
Type of Shoe used <u>guide</u> Float collar used <u>insert</u> Btm 3 jts welded <u>yes</u>					
TD of hole <u>1024'</u> Set <u>1024'</u> Feet of <u>7"</u> Inch <u>20</u> # Grade <u>K-SS</u>					
<u>New</u> -used csg. @ <u>1024'</u> with <u>150</u> sacks neat cement around shoe					
+ <u>250</u> sax <u>C</u> additives _____					
Plug down @ <u>4:00</u> (AM) (PM) <u>PM</u> Date <u>7/21/80</u>					
Cement circulated <u>yes</u> No. of Sacks <u>20 sx</u>					
Cemented by <u>Dowell</u> Witnessed by <u>Mike Stullfield</u>					
Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____					
Casing test @ _____ (AM) (PM) Date _____					
Method Used _____ Witnessed by _____					
Checked for shut off @ _____ (AM) (PM) Date _____					
Method used _____ Witnessed by _____					
Remarks: <u>+ 300 sx 6 5/8" spg. (8# K-SS, 1/4# collo., 370cc.)</u>					
<u>hosted by break w</u>					