

DISTRIBUTION		
SANTA FE	1	
FILE	1	✓
U.S.G.S.		
LAND OFFICE		
OPERATOR	1	

NEW MEXICO OIL CONSERVATION COMMISSION

Supersedes Old  
C-102 and C-103  
Effective 1-1-65

SEP 8 1980

O. C. D.

ARTESIA, OFFICE

5a. Indicate Type of Lease	State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	E 1819

## SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Tenneco Oil Company ✓	8. Farm or Lease Name State JL-36
3. Address of Operator 6800 Park Ten Blvd., San Antonio, Texas 78213	9. Well No. 1
4. Location of Well UNIT LETTER 0 660 FEET FROM THE South LINE AND 1980 FEET FROM THE East LINE, SECTION 36 TOWNSHIP 18S RANGE 29E N.M.P.M.	10. Field and Pool, or Wildcat Und. Turkey Track Morro
15. Elevation (Show whether DF, RT, GR, etc.) 3435'	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Ran 64 jts. of 8-5/8" 32# K55 STC casing set @ 2829.16'. Cemented w/260 sx "C" +2% KCL 14.8 ppg Y-1.32. Cemented w/50 sx "H" + 8% Gel + 10# gilsonite/sx + 4#/sx celloseal + 8%/sx salt. Cemented w/850 sx pacesetter "H" + 8#/sx salt + 1/4#/sx celloseal + 2% CaCl<sub>2</sub>. Cacl top of cement @ surface. Plug down @ 7:55 AM w/1750 psi 8-16-80. WOC -35½ hrs. Tested casing w/1000 psi. OK.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED May Hall TITLE Production Analyst DATE 8-30-80

APPROVED BY W. A. Prescott TITLE SUPERVISOR DATE OCT 22 1980

CONDITIONS OF APPROVAL, IF ANY: