

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐ OCT 7 1982
2. NAME OF OPERATOR
Anadarko Production Company
3. ADDRESS OF OPERATOR
ARTESIA, OFFICE
P. O. Box 67, Loco Hills, New Mexico 88255
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FNL 660' FWL Sec. 17, T18S, R29E
AT TOP PROD. INTERVAL: Same Eddy County, New Mexico
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

- ☐
☐
☐
☐
☐
☐
☐
☐
☐

X Spud, set surface and production casing.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Rigged up rotary tools. Spudded 12 1/4" hole with fresh water @ 9:00 PM 6-11-82. Lost circulation @ 20'. Drilled to 355'.
2. Ran 8-5/8", 24#, K-55 casing with casing shoe @ 349' GL. Halliburton cemented with 300 sx Class H with 2% CaCL; cement did not circulate. PD @ 5:00 PM 6-12-82; ready-mixed with 4 yds cement to surface. Pete Hines with NMOCC witnessed cementing 8-5/8".
3. WOC total of 18 hrs. Installed BOP & pressure tested to 1300# prior to drilling plug with 7-7/8" bit. Drilled to 2810' GL with 10# Brine. Ran 5 1/2", 17#, K-55, LT&C casing with casing shoe @ 2801' GL. Halliburton cemented with 500 sx HL with 8# Salt/sx & 1/2# Flocele/sx and tailed in with 200 sx Class H with .5 of 1% CFR-2, 5# Salt/sx, 10# No. 3 sand/sx & 2% CaCL. Plug Down @ 4:10 PM 6-19-82 - plug held. Arlen Coke with NMOCC witnessed cementing of 5 1/2" casing. Plan braidenhead cement squeeze.
Note: Bennett Wireline Company ran T* Survey 18 hours after PD and found cement top @ 400' GL.

Note: Will file appropriate forms upon completion of well.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Area Supervisor DATE June 22, 1982

ACCEPTED FOR RECORD (This space for Federal or State office use)

APPROVED BY [Signature]
CONDITIONS OF APPROVAL, IF ANY:

OCT 4 1982

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

See Instructions on Reverse Side

JUL 14 1982

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO