Draver / Arte LINITED STAFFES

L	EASE			_

Arte sinitedi Stares	5. LEASE
DEPARTMENT OF THE INTERIOR	NM - 14843
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME Ballard Grayburg San Andres Unit
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas /	Tract 20
well gas other	9. WELL NO.
2. NAME OF OPERATOR	12
Anadarko Production Company	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Loco Hills-Queen-Grayburg San Andre
P. O. Box 67, Loco Hills, New Mexico 88255	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	17 - 18S - 29E
AT SURFACE: 1980 FNLA660 FWL Sec. 17, T185, R29E	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: SameEddy County, New Mexico	Eddy New Mexico
AT TOTAL DEPTH: Same	14. API NO
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT	3524.9' GL
	EIVED
TEST WATER SHUT-OFF	
SHOOT OR ACIDIZE	4.485
REPAIR WELL TAN 2	1 1001: Report results of multiple completion or zone
OLL ON ALTER CASING	Change on Forth 9-330.)
MULTIPLE COMPLETE	
ABANDON*	
(other) X Braidenhead Co	ement Squeeze
including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertiner. Note: Cement did not circulate on primary cement casing. Job was witnessed by Mr. Coke with Verbal permission was received from John Was braidenhead squeeze after a temperature surwith surface casing @ 349'. Note: Cement did not circulate on primary cement witnessed by Mr. Coke with the surface witnessed by Mr. Coke with the surface after a temperature survival with surface casing @ 349'. Note: Cement did not circulate on primary cement witnessed by Mr. Coke with the surface with squeezed with 150 sx Class H cement ISDP = 50#. Left braidenhead shut in over	job on the 5½" production h USGS. ade with USGS to perform a rvey showed cement top @ 400' & pressure of 2 BPM @ 800 psig Final pump pressure = 250#;
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct	,
	or DATE July 12, 1982
SIGNED TITLE ATER SUPERVISOR	UAIE LIFE
ACCEPTED FOR RECORDIS Space for Federal or State off APPROVED(Strig. Sgd.) PETER W. CHESTER TITLE	DATE
CONDITIONS OF APPROVAL IF ANY: 1983	

MINERALS MANAGEMENT SERVICE ROSWELL, NEW MEXICO

*See Instructions on Reverse Side