

OIL CONSERVATION DIVISION

P. O. BOX 2048

SANTA FE, NEW MEXICO 87501

RECEIVED

Form C-103
Revised 10-1-

NO. OF COPIES RECEIVED	
CONTRIBUTOR	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

APR 17 1981

6a. Indicate Type of Lease
State ☒ For ☐

S. State Oil & Gas Lease No.

LG 1270

SUNDRY NOTICES AND REPORTS ON WELLS

ARTESIA, NEW MEXICO

DO NOT USE THIS FORM FOR NOTICES OR REPORTS ON WELLS IN A DIFFERENT RESERVOIR.
USE APPLICATION FOR PERMIT TO DRILL A WELL FOR A DIFFERENT RESERVOIR.

7. Unit Agreement Name

8. Form or Lease Name

State "JM" Com

9. Well No.

2

10. Field and Pool, or Wildcat

Penasco Draw Morrow

12. County

Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐PLUG AND ABANDON ☐REMEDIAL WORK ☐ALTERING CASING ☐TEMPORARILY ABANDON ☐CHANGE PLANS ☐COMMENCE DRILLING OPNS. ☐PLUG AND ABANDONMENT ☐FILL OR ALTER CASING ☐CASING TEST AND CEMENT JOBS ☒OTHER ☐

11. Describe the Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1105.

Spudded a 17-1/2" hole at 9:30 AM 3-10-81. TD 347' - Ran 8 joints of 13-3/8" 48# K-55 ST&C casing set at 347'. Slurry weight 14.8, 1.32 cu ft/sack. Compressive strength at 70 degrees 1023 psi in 12 hours. 1-notched guide shoe at 347'. Flapper insert float at 311'. Cemented w/375 sacks Class C 4% CaCl. PD 8:00 PM 4-10-81. Bumped plug to 500 psi, released pressure & float held okay. Cement circulated 35 sacks to pit. Compressive strength of cement - 1875 psi in 12 hours. WOC 12 hours. Reduced hole to 12-1/4". Drilled plug & resumed drilling. TD 1088' - Ran 27 joints of 8-5/8" 24# K-55 ST&C casing set at 1088'. 1-regular pattern guide shoe at 1088'. Flapper insert float at 1048'. Cemented w/200 sacks Class C 4% CaCl, 800 sacks 65-35 Poz, 4% Bentonite, 8# Kolite, 1/4# celloflakes & 3% CaCl. Tailed in w/150 sacks Class C 2% CaCl. PD 4:00 AM 4-12-81 Bumped plug to 500 psi, released pressure & float held okay. Cement did not circulate. WOC 6 hours. Ran Temperature Survey & found top of cement at 420'. Ran 1". Tagged cement at 397'. Spotted 75 sacks Class C 4% CaCl. PD 11:15 AM 4-12-81. WOC 2 hours. Ran 1". Tagged cement at 357'. Spotted 124 sacks Class C 4% CaCl. PD 2:00 PM 4-12-81. Circulated 15 sacks to pit. WOC 20 hours. NU & tested to 1000 psi, okay. Reduced hole to 7-7/8".

12. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Juanita GoodlettTITLE Engineering SecretaryDATE 4-17-81APPROVED BY Mike WilliamsTITLE OIL AND GAS INSPECTORDATE APR 23 1981

13. CONDITIONS OF APPROVAL, IF ANY: