

- C. If, upon abandonment of wells on Federal surface, the retention of the well pad and/or access road is not considered necessary for the management and multiple use of the natural resources, they will be ripped a minimum of 12" in depth. All ripped surfaces are to be protected from vehicular travel by construction of a dead-end ditch and earthen barricade at the entrance to these ripped areas. (Reseeding of the affected areas may be required.)
- D. Surface restoration after abandonment of wells on non-Federal surface normally will be in accordance with the operator - landowner agreement.
- E. Within 15 days after plugging the well, a Subsequent Report of Abandonment is to be filed on form 9-331 in quintuplicate showing the manner in which the well was plugged, including depths where casing was cut and pulled from, intervals, by depths, where cement plugs were placed, and the date plugging was completed. When all surface restoration work is completed, advise the District Office so that a field inspection of the wellsite can be made.

15. SPECIAL STIPULATIONS:

The following special requirements apply and are effective when check-marked.

- ☒ A. 11 3/4" surface casing should be set in the Rustler Anhydrite formation and cement circulated to the surface. ~~It surface casing is set at a lesser depth, the 8 5/8" casing must be cemented from the casing shoe to the surface or cemented to the surface through a stage tool set at least 50 feet below the top of the Rustler after cementing around the shoe with sufficient cement to fill to the base of the salt section.~~
- ☒ B. Before drilling below the 8 5/8" casing, the blowout preventer assembly will consist of a minimum of one annular type and two ram type preventers.
- ☐ C. Casing protectors will be run on drill pipe while drilling through the \_\_\_\_\_ casing. Protectors will be of sufficient number and of sufficient outside diameter to protect the casing.
- ☐ D. Minimum required fill of cement behind the 8 5/8" casing is to circulated
- ☒ E. After setting the 8 5/8" casing string and before drilling into the WOLF CAMP formation, the blowout preventers and related control equipment shall be pressure tested to rated working pressures by an independent service company. Any equipment failing to test satisfactorily shall be repaired or replaced. This office ~~should be notified in sufficient time for a representative to witness the tests and~~ shall be furnished a copy of the pressure test report.
- Mud system monitoring equipment, with derrick floor indicators and visual and audio alarms, shall be installed and operating before drilling into the WOLF CAMP formation and used until production casing is run and cemented. Monitoring equipment shall consist of the following:
- (1) A recording pit level indicator to determine pit volume gains and losses.
  - (2) A mud volume measuring device for accurately determining mud volume necessary to fill the hole on trips.
  - (3) A flow sensor on the flow-line to warn of any abnormal mud returns from the well.
- ☐ F. For the protection of livestock and wildlife all pits containing toxic liquids will be fenced and covered with a fine mesh netting (i.e. Hardware Cloth) with openings being 1/2 inch or less.