

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 062404

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

"20"
Empire Federal "20"

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

North Turkey Track
Undesignated (Morrow)

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

UL-H

Sec 20, T-18-S, R-29-E

12. COUNTY OR PARISH 13. STATE

Eddy

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL ☐ GAS ☒ OTHER ☐
WELL WELL

2. NAME OF OPERATOR

Southland Royalty Company ✓

3. ADDRESS OF OPERATOR

1100 Wall Towers West Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1980' FNL & 660' FEL, Sec 20, T-18-S, R-29-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3529.6 GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) Set 11 3/4" surface csg

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spud 15" hole @ 11 A.M. 9/15/80. Drill 15" hole to 255'. CCM to run csg. Ran 6 jts of 11 3/4" 42# H-40 csg. Set @ 255'. Cmt w/250 sxs C1 "C" w/2% C.C. Circ 5 sxs but fell back. Fill backside w/4 yards ready mix. WOC 18 hrs. Install 11 3/4" x 12" 3000# head. Install BOP. After 24 hr pressure test BOP & 11 3/4" csg to 1000# for 30 min. Held OK. Compressive strength of C1 "C" w/2% C.C. After 24 hrs is 2015 psi @ 95°F. Drill ahead w/11" bit.

RECEIVED

OCT 2 1980

O. C. D.
ARTESIA, OFFICE

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE District Operation Engineer

DATE 9/17/80

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

SEP 20 1980

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

See Instructions on Reverse Side