

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	1
U.S.O.S.	
LAND OFFICE	
OPERATOR	1

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1

30. Indicate Type of Lease
State ☐ Fee ☒
3. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT TO DRILL OR DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR")

Oil Well ☐ Gas Well ☒ OTHER ☐

Name of Operator
Yates Petroleum Corporation ✓

Address of Operator
207 South 4th St., Artesia, NM 88210

Location of Well
UNIT LETTER **J** **1980** FEET FROM THE **South** LINE AND **1980** FEET FROM
THE **East** LINE, SECTION **34** TOWNSHIP **18S** RANGE **25E** NEARBY

7. Unit Agreement Name
8. Name of Lease Name
Rio Penasco OJ Com
9. Well No.
1
10. Field and Pool, or Whidout
Und. Boyd Morrow
12. County
Eddy

15. Elevation (Show whether DE, RT, GL, etc.)
3485' GR

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

REPAIR REMEDIAL WORK ☐ PROBABLY ABANDON ☐ C OR ALTER CASING ☐ OTHER ☐	PLUG AND ABANDON ☐ CHANGE PLANS ☐ OTHER ☐	REMEDIAL WORK ☐ COMMENCE DRILLING OPER. ☐ Casing Test and Cement Jobs ☐ OTHER <u>Perforate & Treat</u>	ALTERING CASING ☐ PLUG AND ABANDONMENT ☐
--	--	--	---

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE HOLE 1103.

TD 9140'; PBTD 8925'. WIH w/tubing conveyed gun and perforated 8895-8914' w/20 .50" holes as follows: 8895-8901' (12 holes); 8906-8909' (6 holes); 8913-8914' (2 holes). Set packer at 8875'. Acidized perforations 8895-8914' w/1500 gallons 7½ MS acid and nitrogen. Well flowing at 60 psi on 1/2" positive choke. Frac'd perforations 8895-8914' w/20000 gallons MS frac, 30000# sand (5000# 100 mesh and 25000# 20/40 sand) and 7500 gallons CO2. Set standing valve to perforate new zone. WIH w/tubing conveyed gun and set Baker Lok-Set packer at 8828'. Perforated 8850-8855' w/20 .50" holes (4 SPF). Well stabilized at 1100# on 1/2" choke = 7 mmcfpd.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

by W. A. Gressett TITLE Engineering Secretary DATE 3-17-81
by W. A. Gressett TITLE SUPERVISOR DISTRICT II DATE MAR 15 1981
ADDITIONS OF APPROVAL, IF ANY: