

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

RECEIVED

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR  
Yates Petroleum Corporation
3. ADDRESS OF OPERATOR  
207 South 4th St., Artesia, NM 88210
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
1980' FSL & 990' FWL, Sec. 3-18S-25E  
AT SURFACE:  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input checked="" type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>
(other)	<input type="checkbox"/>	<input type="checkbox"/>

- LEASE  
NM 14857
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME  
Murphy NW Federal
9. WELL NO.  
1
10. FIELD OR WILDCAT NAME  
Eagle Creek Permo Penn
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Unit L, Sec. 3-T18S-R25E
12. COUNTY OR PARISH  
Eddy
13. STATE  
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3519.5' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

RECEIVED  
1982

OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Rigged up. WIH with casing gun and perforated 6549-6728' w/23 .50" holes as follows: 6549, 50½, 52, 64, 65, 84, 86, 87½, 89, 91, 6601½, 03, 05, 50, 51, 60, 61, 62, 63, 6725, 26, 27, and 28'. Acidized well w/6500 gallons 15% DS-30 acid in 4 stages: Stage 1: 6584-6605', Stage 2: 6549-65', Stage 3: 6650-63', Stage 4: 6725-28'.  
Set standing valve at 8241'. RBP set at 6770' and packer set at 6531'.

Work began 2-12-82. Completed 4-6-82.

Post FD-2  
10-22-82  
Z TR  
RG-PW

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED David R. Glass TITLE Engineering Secty DATE 8-31-82

ACCEPTED FOR RECORD

(ORIG. SGD.) DAVID R. GLASS  
(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL IF ANY

OCT 12 1982

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

See Instructions on Reverse Side