

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)


1. oil ☒ gas ☐ other ☐2. NAME OF OPERATOR
Yates Petroleum Corporation ✓3. ADDRESS OF OPERATOR
207 South 4th St., Artesia, NM 882104. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 1650 FSL & 990 FWL
AT SURFACE:
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☒
☐
☐
☐
☐
☐
☐
☐U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO5. LEASE
NM 0487738

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Federal AB9. WELL NO.
610. FIELD OR WILDCAT NAME
Penasco Draw SA-Yeso Associated11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Unit L, Sec. 32-18S-25E12. COUNTY OR PARISH
Eddy13. STATE
NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3612' GR

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded a 15" hole at 3:00 PM 10-30-80.

TD 381' Ran 10 joints of 10-3/4" 40.50# K-55 ST&C casing set at 381'. 1-Texas Pattern guide shoe at 381'. 1-flapper inset float at 344'. Cemented w/350 sacks Class "C" 4% CaCl. PD 5:30 PM 10-31-80. Cement circulated 10 sacks. Cement fell back. Filled hole w/3 yards of Ready-Mix. WOC 12 hours. Backed off and reduced hole to 9-1/2". Drilled plug and tested to 600#, OK.

TD 1032' Ran 25 joints of 7" 20# K-55 ST&C casing set at 1032'. 1-Texas Pattern guide at 1032'. 1-flapper insert float at 990'. Cemented w/200 sacks Class "C" Neat, 800 sacks 65-35 Poz, 4% Bentonite, 8# Keolite, 1/4# celloflake and 3% CaCl. Tailed in w/150 sacks Class "C" 2% CaCl. PD 12:30 AM 11-1-80. Cement circulated 25 sacks. Cement fell back and filled hole to surface w/6 yards of Ready Mix. WOC 18 hours. NU and tested to 1500#, OK. Reduced hole to 6-1/4". Drilled plug and tested to 600#, OK.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Albert R. Hall TITLE Engineer DATE Nov. 4, 1980

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: