UNITED STATES	·	- Budget Burea	ed. u No. 42-R1424
DEPARTMENT OF THE INTERIOR	5. LEASE	Λ	
GEOLOGICAL SURVEY	LC-055465- 6. IF INDIAN, AL		BE NAME
		<u></u>	
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEN	IENT NAME	N GCODY
Do not use this form for proposals to drill or to deepen or plug back to a different eservoir. Use Form 9–331–C for such proposals.)			
	8. FARM OR LEA		
1. oil gas well well well other	Federal BA	Com.	10 augus 6
2. NAME OF OPERATOR	3. WELLIND.		
Amoco Production Company	10. FIELD OR WIL	DCAT NAME	
3. ADDRESS OF OPERATOR	Scoggin Dr	aw Morrow	÷ .
P. O. Box 68 Hobbs, NM 88240	11. SEC., T., R., N	I., OR BLK. AN	ID SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA	0.07	
below.) AT SURFACE: 1980' FNL & 760' FWL, Sec. 4	12. COUNTY OR I	8-27 Parish 13. s	TATE
AT TOP PROD. INTERVAL: (Unit E, T-18-S, R-27-E)	Eddv	10. 0	NM
AT TOTAL DEPTH:	14. API NO.		
6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,			
REPORT, OR OTHER DATA	15. ELEVATIONS		DB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	35	86.0'GL	
EST WATER SHUT-OFF			
RACTURE TREAT			
CHOOT OR ACIDIZE	(NOTE: Report res	ite of multiple of	mpletion or zone
PULL OR ALTER CASING		Form 9-330.)	propresion or zone
		1.	
CHANGE ZONES	VELL, MENT MEXICO		· · · ·
other)	MEXICO		
measured and true vertical depths for all markers and zones pertinen Drilled to a TD of 9805' and ran 546' of 5-1/2"	17# N-80, 29		/2"
17# K-55, and 6339' of 5-1/2" 15.5# K-55 casing with 425 SX Trinty Lite with additives and 650 additives. Plugged down at 3:30 a.m. 1-29-81. found TCMT approx. 3800'. WOC 18 hrs. Tested 30 min. and tested OK. Currently waiting on co	SX Class "H" Ran tempera casing with	cement wi ture surve 1000# for	ced ith ey and
17# K-55, and 6339' of 5-1/2" 15.5# K-55 casing with 425 SX Trinty Lite with additives and 650 additives. Plugged down at 3:30 a.m. 1-29-81. found TCMT approx. 3800'. WOC 18 hrs. Tested	SX Class "H" Ran tempera casing with	cement wi ture surve 1000# for	ted ith ay and
17# K-55, and 6339' of 5-1/2" 15.5# K-55 casing with 425 SX Trinty Lite with additives and 650 additives. Plugged down at 3:30 a.m. 1-29-81. found TCMT approx. 3800'. WOC 18 hrs. Tested 30 min. and tested OK. Currently waiting on co 0+4-USGS, A 1-Hou 1-Susp 1-Marathor 1-W. Stafford, Hou	SX Class "H" Ran tempera casing with ompletion uni	cement wi ture surve 1000# for t. 1-Exxon	ted ith ey and 1-GLF
17# K-55, and 6339' of 5-1/2" 15.5# K-55 casing with 425 SX Trinty Lite with additives and 650 additives. Plugged down at 3:30 a.m. 1-29-81. found TCMT approx. 3800'. WOC 18 hrs. Tested 30 min. and tested OK. Currently waiting on co 0+4-USGS, A 1-Hou 1-Susp 1-Marathor	SX Class "H" Ran tempera casing with ompletion uni	cement wi ture surve 1000# for t. 1-Exxon	ted ith ey and 1-GLF
17# K-55, and 6339' of 5-1/2" 15.5# K-55 casing with 425 SX Trinty Lite with additives and 650 additives. Plugged down at 3:30 a.m. 1-29-81. found TCMT approx. 3800'. WOC 18 hrs. Tested 30 min. and tested OK. Currently waiting on co 	SX Class "H" Ran tempera casing with ompletion uni	cement wi ture surve 1000# for t. 1-Exxon	ted ith ey and 1-GLF
17# K-55, and 6339' of 5-1/2" 15.5# K-55 casing with 425 SX Trinty Lite with additives and 650 additives. Plugged down at 3:30 a.m. 1-29-81. found TCMT approx. 3800'. WOC 18 hrs. Tested 30 min. and tested OK. Currently waiting on co 	SX Class "H" Ran tempera casing with ompletion uni	cement wi ture surve 1000# for t. 1-Exxon Set @	ted ith ey and 1-GLF
17# K-55, and 6339' of 5-1/2" 15.5# K-55 casing with 425 SX Trinty Lite with additives and 650 additives. Plugged down at 3:30 a.m. 1-29-81. found TCMT approx. 3800'. WOC 18 hrs. Tested 30 min. and tested OK. Currently waiting on co 0+4-USGS, A 1-Hou 1-Susp 1-Marathor 1-W. Stafford, Hou Subsurface Safety Valve: Manu. and Type 18. Thereby certify that the foregoing is true and correct SIGNED	SX Class "H" Ran tempera casing with ompletion uni n l-Bass	cement wi ture surve 1000# for t. 1-Exxon Set @	ted ith ey and 1-GLF
17# K-55, and 6339' of 5-1/2" 15.5# K-55 casing with 425 SX Trinty Lite with additives and 650 additives. Plugged down at 3:30 a.m. 1-29-81. found TCMT approx. 3800'. WOC 18 hrs. Tested 30 min. and tested OK. Currently waiting on co 0+4-USGS, A 1-Hou 1-Susp 1-Marathor 1-W. Stafford, Hou Subsurface Safety Valve: Manu. and Type 18. Thereby certify that the foregoing is true and correct SIGNED	SX Class "H" Ran tempera casing with ompletion uni n l-Bass	cement wi ture surve 1000# for t. 1-Exxon Set @	ted ith ey and 1-GLF
17# K-55, and 6339' of 5-1/2" 15.5# K-55 casing with 425 SX Trinty Lite with additives and 650 additives. Plugged down at 3:30 a.m. 1-29-81. found TCMT approx. 3800'. WOC 18 hrs. Tested 30 min. and tested OK. Currently waiting on co 0+4-USGS, A 1-Hou 1-Susp 1-Marathor 1-W. Stafford, Hou Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct SIGNED	SX Class "H" Ran tempera casing with ompletion uni n 1-Bass / <u>St</u>	cement wi ture surve 1000# for t. 1-Exxon 	ted ith ey and 1-GLF Ft.
17# K-55, and 6339' of 5-1/2" 15.5# K-55 casing with 425 SX Trinty Lite with additives and 650 additives. Plugged down at 3:30 a.m. 1-29-81. found TCMT approx. 3800'. WOC 18 hrs. Tested 30 min. and tested OK. Currently waiting on co 0+4-USGS, A 1-Hou 1-Susp 1-Marathor 1-W. Stafford, Hou Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct SIGNED	SX Class "H" Ran tempera casing with ompletion uni n 1-Bass / <u>St</u>	cement wi ture surve 1000# for t. 1-Exxon 	ted ith ey and 1-GLF Ft.
17# K-55, and 6339' of 5-1/2" 15.5# K-55 casing with 425 SX Trinty Lite with additives and 650 additives. Plugged down at 3:30 a.m. 1-29-81. found TCMT approx. 3800'. WOC 18 hrs. Tested 30 min. and tested OK. Currently waiting on co 0+4-USGS, A 1-Hou 1-Susp 1-Marathor 0+4-USGS, A 1-Hou 1-Susp 1-Marathor 1-W. Stafford, Hou Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct Subsurface Dependence TITLE Admin. Analy ACCEPTFD FOR RECORD TITLE Admin. Analy PETER W. CHECORD TITLE Marathor	SX Class "H" Ran tempera casing with ompletion uni n 1-Bass / <u>St</u>	cement wi ture surve 1000# for t. 1-Exxon 	ted ith ey and 1-GLF Ft.

- ,

-/SF