Ň.M.Ö.C.D. COPY Form 9-331 Form Approved. Dec. 1973 Budget Bureau No. 42-R1424 **UNITED STATES** 5. LEASE DEPARTMENT OF THE INTERIOR c/5F NM-12676 **GEOLOGICAL SURVEY** 6. IF INDIAN, ALLOTTEE OR TRIBE NAME 7. UNIT AGREEMENT NAME SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.) 8. FARM OR LEASE NAME Froehlich Federal gas well X other well 9. WELL NO. 2. NAME OF OPERATOR CARBONIT EXPLORATION, INC. 10. FIELD OR WILDCAT NAME 3. ADDRESS OF OPERATOR 77063 Undesignated Wildcat Aba 8989 Westheimer, Suite 106, Houston, Texas 11. SEC., T., R., M., OR BLK. AND SURVEY OR 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 AREA 11t-H below.) Section 24, T-18-S. R-21-E AT SURFACE: 1980' FNL & 660' FEL of Section 24 12. COUNTY OR PARISH 13. STATE AT TOP PROD. INTERVAL: Eddy New Mexico AT TOTAL DEPTH: 14. API NO. 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 15. ELEVATIONS (SHOW DF, KDB, AND WD) 4073' G.L. REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL Report results of multiple completion or zone PULL OR ALTER CASING change on Form 9-330.) MULTIPLE COMPLETE **CHANGE ZONES** ABANDON* (other) (other) Surface casing and cementing

S. GEOLOGIOM MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Charty state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical deaths for all produces. Surface casing and cementing measured and true vertical depths for all markers and zones pertinent to this work.)* Spudded November 28, 1980, 17 1/2" hole to 200'. Ran 7 jts., 13 3/8", 48#, H-40 casing. Set casing at 200'. **RECEIVED** Halliburton cemented with 200 sx Class "C" with 2% CaCl. APR 06 1981 Plug down at 8 P.M., January 29, 1981. Cement did not circulate. O. C. D. On January 30, 1981 finished cementing back to surface ARTESIA, OFFICE with 14 yards ready-mix.

Subsurface Safety Valve: Manu. and Type	Set @	Ft
18. I hereby certify that the foregoing is true and correct		
SIGNED L. S. Green for Bill Boken. Agent	DATE 20 March 1981	
ACCEPTED FOR RECORD pade for Federal or State office	use)	
APPROVED BYPETER W. CHESTER TITLE	DATE	
APR 3 1981		
U.S. GEOLOGICAL SURVEY	_	

ROSWELL, NEW MEXIC

L.S. Highwardal Shingy AMERIA, REVISEROS