

OIL CONSERVATION DIVISION

P. O. BOX 2080

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>

5. State Oil & Gas Lease No.
LG 827

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

7. Unit Agreement Name

8. Farm or Lease Name

Arnold OR State

9. Well No.

1

10. Field and Pool, or Wildcat

Und. Morrow

12. County

Eddy

15. Elevation (Show whether DF, RT, GR, etc.)

3748' GR

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
 ABANDON ☐
 ALTER CASING ☐

PLUG AND ABANDON ☐
 CHANGE PLANS ☐

REMEDIAL WORK ☐
 COMMENCE DRILLING OPS. ☐
 CASING TEST AND CEMENT JOBS ☒
 OTHER ☐

ALTERING CASING ☐
 PLUG AND ABANDONMENT ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed operations) SEE RULE 1103.

Spudded a 17-1/2" hole at 11:30 PM 1-15-81.

PD 438' Ran 10 joints of 13-3/8" ST&C 54.50# casing set at 438'. 1-ball float shoe set at 438'. Cemented w/450 sacks Class "C" 4% CaCl. Slurry weight 14.8, 1.32 cu/ft sack. Compressive strength at 70 degrees 1023 psi in 8 hours. PD 1:10 PM 1-16-81. Bumped plug to 500 psi, released pressure and float held okay. Cement circulated 30 sacks to bit. Compressive strength of cement - 1850 psi in 12 hours. WOC 12 hours. Reduced hole to 12-1/4". Drilled plug and resumed drilling.

PD 988' Ran 25 joints of 8-5/8" 24# K-55 ST&C casing set at 988'. 1-Texas Pattern guide shoe at 988'. Flapper insert float at 948'. Cemented w/350 sacks 65-35 Poz, 6% Bentonite, 1/4# Kolite, 1/4# celloflakes and 3% CaCl. Tailed in w/150 sacks Class "C" 2% CaCl. PD 11:00 AM 1-18-81. Bumped plug to 500 psi, released pressure and float held okay. Cement circulated 50 sacks. WOC 18 hours. Nippled up and tested to 1500 psi, OK. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Ganita Doodlett

TITLE Engineering Secretary

DATE Jan. 20, 1981

Mike Williams

TITLE OIL AND GAS INSPECTOR

DATE JAN 23 1981

COPIES OF APPROVAL, IF ANY: