

OIL CONSERVATION DIVISION

P. O. BOX 2080

SANTA FE, NEW MEXICO 87501

FEB 12 1981

Form C-103
Revised 10-

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	
U.S.G.B.	
LAND OFFICE	
OPERATOR	1

O. C. D.
ARTESIA, OFFICE

5a. Indicate Type of Lease	State ☒ Fee
5. State Oil & Gas Lease No.	LG 827

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER-	7. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation ✓	8. Farm or Lease Name Arnold OR State Com
3. Address of Operator 207 South 4th St., Artesia, NM 88210	9. Well No. 1
4. Location of Well UNIT LETTER 0 660 FEET FROM THE South LINE AND 1980 FEET FROM THE East LINE, SECTION 34 TOWNSHIP 18S RANGE 24E NMPM.	10. Field and Pool, or Wildcat Und. Morrow
15. Elevation (Show whether DF, RT, GR, etc.) 3748' GR	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPS. ☐	PLUG AND ABANDONMENT ☐
PLUG & ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☐	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any prop. work) SEE RULE 1103.

TD 9050' Ran 219 joints of 5-1/2" 17# & 15.5# K-55 & N-80 casing as follows: 10 joints of 5-1/2" 17# N-80 LT&C, 63 joints of 5-1/2" 17# K-55 LT&C, 114 joints of 5-1/2" 15.5# K-55, 15 joints of 5-1/2" 15.5# K-55 LT&C, 17 joints of 5-1/2" 17# K-55 LT&C casing set at 9017'. 1-Regular Pattern guide shoe at 9017'. Diff-fill float at 8975'. Cemented w/25 sacks 75-25 Poz, 6/10% D-112, 3/10% D-65 & 5#/sack KCL, 575 sacks 50-50 Poz, 6/10% D-112, 3/10% D-65 & 5#/sack KCL. Tailed in w/150 sacks Class H, 6/10% D-112, 3/10% D-65 & 5#/sack KCL. PD 12:00 noon 2-9-81. Bumped plug to 2000 psi, released pressure & float held okay. WOC. Ran Temperature Survey & found top of cement - weak indication at 3700' and definite indication at 4875'. PBTD 8989'.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Joanna Gonzalez</u>	TITLE <u>Engineering Secretary</u>	DATE <u>Feb. 11, 1981</u>
APPROVED BY <u>W.A. Gussert</u>	TITLE <u>SUPERVISOR, DISTRICT 7</u>	DATE <u>FEB 16 1981</u>

CONDITIONS OF APPROVAL, IF ANY: