

UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

NM OIL CONS. COMMISSION
SUBMIT IN 1. LICATE.
Dress (Other) Instructions on re-
verse side)
Artesia, NM 88210

Approved.
Budget Bureau No. 42-B1424

5. LEASE DESIGNATION AND SERIAL NO.

LC-062404

6. IF INDIAN, ALLOTMENT OR TRIBE NAME
DEC 29 1981

7. UNIT AGREEMENT NAME
ARTESIA, OFFICE

8. FARM OR LEASE NAME

Hewitt Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Loco Hills Q/G/SA

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 20, T-18S, R-29E

12. COUNTY OR PARISH 13. STATE

Eddy New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Ray Westall

3. ADDRESS OF OPERATOR

P.O. Box 4 Loco Hills, NM 88255

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

Unit Letter G 2310 FEL 2310 FNL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3617.1

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

Spudding & running 8 5/8" & 4 1/2" csg

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

6-27-81 -- Spud well with 12 1/2" bit. Changed to 7 7/8" bit on 6-28-81. Ran 361' of 8 5/8" OD, 8 rd, 20# casing. Cemented with 350 sx Class "C", 4% CCL. Circulated to surface. WOC 18 hrs. Pressured up to 1000# for 30 minutes. Held OK.

7-3-81 --- TD 3100'. Ran 3084' of 4 1/2" 9-5, 8 rd casing. Set & cemented with 525 sx of Class "C" and 360 sx of 50/50 Poz & 2% KCL. Cement circulated to surface. Float held. WOC 24 hrs.

RECEIVED
DEC 23 1981

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Ray Westall

TITLE

Operator

DATE

12-21-81

(This space for Federal Approval or RECORD)

APPROVED BY

PETER W. CHESTER

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

DEC 28 1981

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

See Instructions on Reverse Side