

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and mud-sensitivity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depth shall also be reported. For multiple completions, Items 30, through 34 shall be reported for each zone. The form is to be filed in quadrants except in state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anby	T. Canyon	T. Ojo Alamo	T. Penn. "H"
T. Salt	T. Strawn	T. Kirtland-Fruitland	T. Penn. "CM"
B. Salt	T. Atoka	T. Pictured Cliffs	T. Penn. "B"
T. Yates	T. Miss.	T. Cliff House	T. Leadville
T. 7 Rivers	T. Devonian	T. Menefee	T. Madison
T. Queen	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg	T. Montoya	T. Mancos	T. McCracken
T. San Andres 1140'	T. Simpson	T. Gallup	T. Ignacio Quartz
T. Glorieta	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T.
T. Ellersbry	T. Gr. Wash	T. Morrison	T.
T. Tubb	T. Granite	T. Todilto	T.
T. Drinkard	T. Delaware Sand	T. Entrada	T.
T. Ann	T. Bone Springs	T. Wingate	T.
T. Wolfcamp	T.	T. Chinle	T.
T. Penn	T.	T. Permian	T.
T. Cisco (Rough C)	T.	T. Penn. "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from 1230 to 1304	No. 2, from 1457 to 1752	No. 3, from to	No. 4, from to
No. 5, from to	No. 6, from to		

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 250 to 285 feet	No. 2, from 407 to 490 feet	No. 3, from 720 to 935 feet	No. 4, from to feet
-----------------------------	-----------------------------	-----------------------------	---------------------

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	250	250	Gravel&Redbeds				
250	285	35	Sand				
285	407	22	Lm.& Anhydrite				
407	490	83	sand				
490	535	45	Lime				
535	650	115	lm.& Sand				
650	720	70	Lime				
720	935	215	Sand& Lime				
935	1800	865	Lime/Dolomite&Shale Stringers				