

10.C.D. COPY

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR
Yates Petroleum Corporation
3. ADDRESS OF OPERATOR
207 South 4th St., Artesia, NM 88210
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FNL & 660' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>
(other) Perforate & Treat		

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 8670'; PBTD 8594'- WIH w/casing gun on wireline & perforated 8302-8330' w/6 .32" holes as follows: 8302-06' w/4 holes & 8328-30' w/2 holes. Ran packer & tubing dry. Set packer at 8248'. Acidized perfs w/1500 gallons 15% DS-30 acid & nitrogen plus ball sealers. Swabbed well dry. Pulled tubing & packer. WIH w/Hollow Steel Strip gun on wireline & perforated 8240-8262' w/12 .40" holes as follows: 8240-44' (5 holes) & 8256-62' (7 holes). Ran packer & RBP. Set RBP at 8286' & packer at 8196'. Swabbed well. Acidized perforations w/1500 gallons 20% DS-30 acid & nitrogen plus ball sealers. Moved RBP & set at 8358'. Moved packer above all perfs & set at 8196'. Flanged up & swabbed well. Frac'd perforations (Atoka) 8240-8330' w/30000 gallons gel KCL water, 15000 gallons CO₂, 45750# 20/40 sand. Well flowed & stabilized at 65# on 1/2" choke = 500 mcfpd.

Note: PBTD corrected from 8662' to 8594'.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Pamela Goodlett TITLE Engineering Secretary DATE 4-22-81

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

PETER W. CHESTER

APR 24 1981

U.S. GEOLOGICAL SURVEY
ROSVILL, NEW MEXICO

*See Instructions on Reverse Side

5. LEASE

NM-0487738

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

RECEIVED

8. FARM OR LEASE NAME

Federal AB Can. APR 2 1981

9. WELL NO.

7

10. FIELD OR WILDCAT NAME

Richard Knob-Atoka Morrow

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Unit E, Sec. 9-T18S-R25E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3573' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)