NM OIL CONS COMMISSION Drawer DD Artesia, NM 88210

Form 3160-5 (June 1990)

12.

☐ Final Abandonment Notice

Notice of Intent

XX Subsequent Report

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993

5. Lease Designation and Serial No. NM 0487738

6. If Indian, Allottee or Tribe Name

KX Change of Plans

New Construction

Water Shut-Off

→ Dispose Water

Non-Routine Fracturing

Conversion to Injection

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLIC

give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Use "APPLICATION FOR	PERMIT— for such proposals RECEIVED	
SUBMIT IN TRIPLICATE		7. If Unit or CA, Agreement Designation
1. Type of Well Oil X Gas Well X Other RECOMPLET 2. Name of Operator	O. C. D.	8. Well Name and No. Federal AB #7
YATES PETROLEUM CORPORATION (505) 748-147ARYESIA, OFFICE 3. Address and Telephone No. 105 South 4th St., Artesia, NM 88210		9. API Well No. 30-015-23646 10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey Desc 1980' FNL, 660' FWL, Sec. 9-T1	•	Undes. Cisco 11. County or Parish, State Eddy, NM
12. CHECK APPROPRIATE BOX(s)	TO INDICATE NATURE OF NOTICE, REPO	RT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled,

Other

Abandonment Recompletion

Plugging Back

Casing Repair

Altering Casing

Propose to abandon Atoka completion 8240-8330' and recomplete in Cisco. 5-6-94. Verbal permission obtained from Shannon Shaw, BLM, Carlsbad, NM, by Darrick Stallings, Yates Petroleum Corporation to change plans as follows:*

- Rig up. Nipple up and test BOP. POOH with tubing, packer and RBP. Set RBP* at 8200'±.
- RIH with 3-1/8" casing gun and perforate Cisco 6822-6830', 6839-6844' and 6859-6863' with 2 SPF.
- RIH w/packer and tubing. Acidize Cisco perfs 6822-6863' with 4000 gals 15% NEFE HCL acid and ball sealers.
- Swab test for recompletion.

· · · · · · · · · · · · · · · · · · ·			
(4. I hereb) certify that the foregoing is true and correct Signed Apole On Allet	_ Title _F	Production Supervisor	Date 5-6-94
Approved by COPIC SCD 105 G. LARA Conditions of approval, if any:	Title	PETROLEUM ENGINEER	Date <u>5/23/94</u>
Conditions of approval, a any.			