

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY**

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR  
Tenneco Oil Company /
3. ADDRESS OF OPERATOR  
6800 Park Ten Blvd. Suite 200, S.A. 78216
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 2040' FWL & 760' FNL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>

(other) Ran and cemented 8-5/8" casing

5. LEASE NM-11326	
6. IF INDIAN, ALLOTTEE OR TRIBE NAME NA	
7. UNIT AGREEMENT NAME NA	
8. FARM OR LEASE NAME McMillian JN-33	
9. WELL NO. 1	
10. FIELD OR WILDCAT NAME <u>Und. Wildcat East Otter Mountain</u>	
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 33, T18S, R27E	
12. COUNTY OR PARISH Eddy	13. STATE New Mexico
14. API NO.	
15. ELEVATIONS (SHOW DF, KDB, AND WD) 3380' GR	

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

2-21-81

Ran 48 jts. of 8-5/8" 32# K-55 8Rd STC casing set @ 1982'. Cemented w/350 sks Class "C" + 1% CaCl followed with 1300 sks Pacsetter lite + 8#/sx salt + 1#/sk perma-check + 1/4#/sk cello + 1% CaCl<sub>2</sub>. Circulated approximately 200 sks to surface. Plug down @ 2AM w/1100 psi on 2-28-81. WOC - 26 hrs.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED *Mary Hall* TITLE Production Analyst DATE 3-4-81

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD  
(This space for Federal or State office use)

PETER W. CHESTER

MAR 10 1981

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

See Instructions on Reverse Side

