

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Yates Petroleum Corp</u>		Lease <u>Nix PK</u>		Well # <u>1</u>	
Location of Well	Unit <u>1650S 1650E J</u>	Section <u>27</u>	Township <u>18</u>	Range <u>26</u>	County <u>Eddy</u>
Drilling Contractor	<u>Artesia Fishing Tool</u>		Type of Equipment <u>Rotary ASAP</u>		

* Witness

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>9 1/2</u>	<u>7"</u>	<u>20#</u>		<u>1120'</u>	<u>550 SX Circ</u>
<u>6 1/4</u>	<u>4 1/2"</u>	<u>9.5#</u>		<u>3250'</u>	<u>300 SX Circ</u>

Casing Data:

Surface 27 joints of 7 inch 23 # Grade
BWW (Approved) (Rejected)

Inspected by _____ date _____

Cementing Program

Size of hole 9 1/8 Size of Casing 7 Sacks cement required _____

Type of Shoe used Guides Float collar used Insert Btm 3 jts welded Yes

TD of hole 1125 Set 1126 Feet of 7 Inch 23 # Grade K55

New-~~used~~ csg. @ 1126 with 150 sacks neat cement around shoe

+ 400 sax 65-35 Pos Mix additives 4% T-1, 8% B. Colite 1/4 Flo Sul 3% CC

Plug down @ 3.45 (AM) (PM) Date 3-2-81

Cement circulated lyc No. of Sacks 40

Cemented by Dowell Witnessed by BW Weaver

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: Last Drilling Break @ 10:15