

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 10
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Yates Petroleum Corp</u>		Lease <u>Nix PK</u>		Well # <u>2</u>	
Location of Well	Unit <u>3303 1650E 0</u>	Section <u>27</u>	Township <u>18</u>	Range <u>26</u>	County <u>Eddy</u>
Drilling Contractor <u>Stewart Bros</u>			Type of Equipment <u>Rotary ASAP</u>		
* Witness					
<u>APPROVED CASING PROGRAM</u>					

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>9 1/2</u>	<u>7"</u>	<u>20#</u>		<u>1120'</u>	<u>550 SK Circ</u>
<u>6 1/4</u>	<u>4 1/2"</u>	<u>9.5#</u>		<u>3250'</u>	<u>300 SK Circ</u>

* Casing Data:

Surface 28 joints of 7 inch 20 # Grade K-55

yes (Approved) (Rejected)

Inspected by B. W. Weaver date 11-7-81

Cementing Program

Size of hole 4 1/2 Size of Casing 7 Sacks cement required

Type of Shoe used Tex Pat Float collar used Insert Btm 3 jts welded yes

TD of hole 1114 Set 1120 Feet of 7 Inch 20 # Grade K-55

New-used csg. @ 1120 with 550 sacks neat cement around shoe

+ sax additives

Plug down @ 7.00 (AM) (PM) Date 11-7-81

Cement circulated yes No. of Sacks 50

Cemented by Denton Witnessed by B. W. Weaver

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: