	-
Form 9-331 N.I.T. O.().15	Form Approved.
Dec. 1973 UNITED STATES	
DEPARTMENT OF THE INTERIOR	5. LEASE 1.0 050906
	LO 050906 6. IF INDIAN, ALLOTTEE OR TRIBE NAME
GEOLOGICAL SURVEY	
SUNDRY NOTICES AND REPORTS ON WEL	LS 7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepen or plug back to a di reservoir. Use Form 9–331–C for such proposals.)	ifferent Ballard Grayburg San Andres Whit
1. oil gas well 🔽 well 🗆 other	Tract No. 5 SEP 1 1981
2. NAME OF OPERATOR	16
Anadarko Froduction Company	10. FIELD OR WILDCAT NAME ADTICIAL OFFICE
3. ADDRESS OF OPERATOR	Loco Hills-Queen-GB-SA
Box 67, Loco Hills, New Mexico	II. SEC., I., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See spa	
below.) AT SURFACE:400' FSL & 2130' FEL Sec.8,TLE	$\frac{8 - 185 - 298}{13 - 510}$
	N. Mex. Eddy New Mexico
AT TOTAL DEPTH: Same	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NO	DTICE,
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT (3507.3' GL
	And a set of the set o
FRACTURE TREAT	15/1/25/11
SHOOT OR ACIDIZE	
PULL OR ALTER CASING	2.8.1961 Children from 9-330.)
	DIL & GAS
	L, NEW MEXICO ·
	·
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and	
including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*	
1. Ferforated 2 squeeze holes @ 1712' KH	
2. Halliburton pressured to 3300# could not pump into perforations.	
3. GEO Vann ran a Cement Top Log from 1800' KB to surface, found Cement Top	
15' KB (2.5'GL). Good cement bond 1800' to 170' w/fair bond from 170' to surface.	
NOTE: Therefore concluded Bennett Wire Line T ⁰ Survey dated 6-15-81 was mis-	
interpreted. Had previously considered Cement Top at 1700' GL (1712' KB).	
See attached: Cement Top Log & T Survey.	
4. Rigged up pulling unit.	
5. Ferforated Grayburg.	
o. Acidized & Fracture treated Grayburg	
7. Installed Production equipment & place	sed werr on pump.
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct	
	nemit gon
SIGNED FOR RECORD TITLE A FBA SU	pervisor DATE August 21, 1981
AGGER A. CHAPMAN (This space for Federal or	
	DATE
COMULTIONS OF APPROVAL, IF ANY: AUG 2 8 1981	
100 4 0 198]	
JUS DA HONOR	
U.S. GEOLOGICAL SURVEY	Reverse Side
POSWELL, NEW AEXICO	

--