

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPL
(Other instructions
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-029415-B RECEIVED

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

FEB 24 1982

7. UNIT AGREEMENT NAME

O. C. O.

8. FARM OR LEASE NAME

Puckett "B"

9. WELL NO.

30

10. FIELD AND POOL, OR WILDCAT

Maljamar (G-SA)

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 25-17S-31E

12. COUNTY OR PARISH 13. STATE

Eddy

New Mexico

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

WILLIAM A. & EDWARD R. HUDSON

3. ADDRESS OF OPERATOR

Box #198, Artesia, New Mexico 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)

At surface 2615' from south and 380' from east lines
Section 25-17S-31E.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

Cement Casing

REPAIRING WELL

ALTERING CASING

ABANDONMENT*


X

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On Dec. 13, 1981, cemented 8-5/8" O.D. J-55 casing at 778' with 600 sx. class C cement with 2% CaCl. Top 34' of casing is 32# and bottom 90' is 32#. Remainder is 24#. Cement circulated.

On Dec. 19, 1981, cemented 5 1/2" O.D. 15.5# J-55 casing at 3890' with 365 sx. 50/50 pozmix cement. Used 15 centralizers and 612' of ruff-coat on bottom of casing. Ran temperature survey. Found top of cement behind 5 1/2" at 2080'.



U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED Ralph L. May TITLE Consulting Engineer

DATE Jan. 25, 1982

(This space for Federal or State office use)

APPROVED BY ROBERT A. CHAPMAN
CONDITIONS OF APPROVAL, IF ANY:

DATE

FEB 2 1982

*See Instructions on Reverse Side

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO