

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TR
(Other instructions
reverse side)

CATE
on re

Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

LC-029415-B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. ☒ OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR

WILLIAM A. & EDWARD R. HUDSON

3. ADDRESS OF OPERATOR

Box #198, Artesia, New Mexico 88210

LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)

At surface

2615' from south and 380' from east lines of
Section 25-17S-31E.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

388 1.3' GR

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Puckett "B"

9. WELL NO.

30

10. FIELD AND POOL, OR WILDCAT

Maljamar - G-SA

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 25-17S-31E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On June 14, 1982, perforated 5½" casing at 3652-54, 3657-59, 3663-84 and 3691-96 with one shot/ft. Set bridge plug at 3710'. Dumped 5' sand on top of B.P. Acidized with 1,000 gals. 15% acid, using 45 ball sealers (balled out). Broke at 2800 psi. Treated at 2500 psi. at 5 BPM.

On June 16, 1982, fraced perfs with 6,000 gals. 20% acid duo-frac + 10,250 gals. redi-frac gel + 8,000# FLA-100 sand + Protex-A11 and tailed in with corrosion inhibitor. Treated in 2 stages, using 200# rock salt and 100# benzoic acid as diverter plug.

Before treatment, well pumped 33 BO + 13 BWPD. On June 24, 1982, well pumped 80 BO + 25 BWPD.

RECEIVED

AUG 16 1982

OIL & GAS
MINERALS MGMT. SERVICE
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Ralph L. Gray

TITLE Consulting Engineer

DATE Aug. 16, 1982

(This space for Federal use)

ACCEPTED FOR RECORD

(ORIG. SGD.) DAVID R. GLASS

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

OCT 13 1982

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side