

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐
2. NAME OF OPERATOR
Holly Energy Inc.
3. ADDRESS OF OPERATOR
P.O. Box 726 Artesia, New Mexico
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface 990'FNL 330'FEL Sec 3 T-18S R-30E

14. PERMIT NO.
15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3570.2

5. LEASE DESIGNATION AND SERIAL NO.
NM 01159
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Nelson
9. WELL NO.
O. C. D.
7 ARTESIA, OFFICE
10. FIELD AND POOL OR WILDCAT
Grayburg-San Andres
Loco Hills Queen
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec 3 T-18S R-30E
12. COUNTY OR PARISH
Eddy
13. STATE
NM

RECEIVED

SEP 22 1981

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
(Other) ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
ABANDON* ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐
FRACTURE TREATMENT ☐
SHOOTING OR ACIDIZING ☐
(Other) ☒ Set production casing
(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL ☐
ALTERING CASING ☐
ABANDONMENT* ☒

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drill 7-7/8" hole to 3800' set 3796' 4 1/2" 10.5 K-55 STC casing. w/ DV tool @ 2930'.
Cement w/250 sacks 65/35 Class C poz, 4% Bentonite, 3% Calcium chloride.
1st stage plug down @ 9:45 p.m. 8-6-81
Open DV tool Circulate 8 hours. Cement 2nd stage w/400 sacks RFC, 3% calcium.
Plug down @ 6:30 a.m. 8-7-81

RECEIVED
SEP 17 1981

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED ACCEPTED FOR RECORD
ROGER A. CHAPMAN

TITLE Superintendent

DATE 9-8-81

(This space for Federal or State office use)

APPROVED BY SEP 18 1981
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____

U.S. GEOLOGICAL SURVEY,
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side

