

C158
Up

OIL CONSERVATION DIVISION

DISTRICT I
P. O. Box 1980 Hobbs, NM 88240

P. O. Box 2088
Santa Fe, New Mexico 87504-2088

DISTRICT II
P. O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd, Aztec, NM 87410

Well API NO. 30-015-23859
5. Indicate Type or Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. B-11594-2
7. Lease Name or Unit Agreement Name TRAVIS DEEP OHIO COM.
8. Well No. # 1
9. Pool name or Wildcat EMPIRE MORROW, SOUTH

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well OIL <input type="checkbox"/> GAS <input checked="" type="checkbox"/> WELL WELL OTHER
2. Name of Operator Harvey E. Yates Company
3. Address of Operator P.O. Box 1933, Roswell, NM 88202 1-505-623-6601

4. Well Location Unit Letter M : 760 Feet From The SOUTH Line and 660 Feet From The WEST Line
Section 13 Township 18S Range 28E NMPM EDDY County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3539.1' GL

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK <input type="checkbox"/> PLUG AND ABANDON <input checked="" type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER: <input type="checkbox"/>	SUBSEQUENT REPORT OF: REMEDIAL WORK <input type="checkbox"/> ALTERING CASING <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> PLUG AND ABANDONMENT <input type="checkbox"/> CASING TEST AND CEMENT JOB <input type="checkbox"/> OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work.) SEE RULE 1103

CURRENT STATUS: SI PRIOR PERFS: 10,709-756' (OA) MORROW
9-2-98 SET 4 1/2" CIBP @ 10,599' PLUS 2 RUNS CEMENT (35') PBD 10,564'.
TOC @ 8328' BY CBL
SPOT 25 SK PLUG @ 8500' (EST 250' PLUG w/ TOP @ 8250') T.B.S. - 6205'
PERF SQZ HOLES @ 5500' & SPOT 35 SK PLUG. * Perf. sqz holes 6255'. Squeeze cement plug insides outside 4 1/2" sq.
CUT & PULL CASING @ 3100' (14' INSIDE INTERMEDIATE PIPE) * Cut & Pull casing @ 3164' so below 8 1/2" csg shoe.
SPOT 100' PLUG (50' IN & 50' OUT OF CUTOFF) & TAG * 100' cement Plug @ 393'-293'
SPOT 10 SK SURFACE PLUG.
INSTALL DRY HOLE MARKER
CUT OFF ANCHORS
BACKFILL WORK PIT & CLEAN LOCATION.

* Brine gel between all cement Plugs.
* Notifie NMACD to witness Plugging Operations

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Ray F. Nokes TITLE PROD. MGR. / ENGINEER. Date 10/8/98
TYPE OR PRINT NAME RAY F. NOKES TELEPHONE NO. 1-505-623-6601

(This space for State use)

Approved by Mr. Shopshire Title Field Rep. II Date Oct. 16-98
Conditions of approval, if any: