

OIL CONSERVATION DIVISION

DISTRICT I  
P. O. Box 1980 Hobbs, NM 88240

P. O. Box 2088  
Santa Fe, New Mexico 87504-2088

DISTRICT II  
P. O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd, Aztec, NM 87410

Well API NO.	30-015-23859
5. Indicate Type or Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	B-11594-2
7. Lease Name or Unit Agreement Name	TRAVIS DEEP OHIO COM.
8. Well No.	# 1
9. Pool name or Wildcat	EMPIRE MORROW, SOUTH

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well OIL <input type="checkbox"/> GAS <input checked="" type="checkbox"/> WELL WELL OTHER	2. Name of Operator Harvey E. Yates Company
3. Address of Operator P.O. Box 1933, Roswell, NM 88202 1-505-623-6601	4. Well Location Unit Letter M : 760 Feet From The SOUTH Line and 660 Feet From The WEST Line Section 13 Township 18S Range 28E NMPM EDDY County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3539.1' GL	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER: <input type="checkbox"/>	SUBSEQUENT REPORT OF: REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> CASING TEST AND CEMENT JOB <input type="checkbox"/> OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work.) SEE RULE 1103

CURRENT STATUS: SI PRIOR PERFS: 10,709-756' (OA) MORROW  
9-2-98 SET 4 1/2" CIBP @ 10,599' PLUS 2 RUNS CEMENT (35') PBTD 10,564'.  
TOC @ 8328' BY CBL  
SPOT 25 SK PLUG @ 8500' (EST 250' PLUG w/ TOP @ 8250')  
PERF SQZ HOLES @ 5500' & SPOT 35 SK PLUG. \* Perf. Sqz Holes @ 6255'. Squeeze 100' int Plugs inside & outside  
CUT & PULL CASING @ 3100' (14' INSIDE INTERMEDIATE PIPE) csj. TAG  
SPOT 100' PLUG (50' IN & 50' OUT OF CUTOFF) & TAG  
SPOT 10 SK SURFACE PLUG. \* Cut & Pull 5 1/2" csj @ 3164'.  
INSTALL DRY HOLE MARKER Spot 100' int Plug 3214' 3064' TAG  
CUT OFF ANCHORS \* 100' cement Plug 393' 293'.  
BACKFILL WORK PIT & CLEAN LOCATION.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Ray F. Nokes TITLE PROD. MGR. / ENGINEER. Date 12/30/99  
TYPE OR PRINT NAME RAY F. NOKES TELEPHONE NO. 1-505-623-6601

(This space for State use)

Approved by Mike S. Tullfield Title Field Rep II Date 1/3/2000

Conditions of approval, if any:

\* Brine gel. between all cement plugs.  
\* Notify N.M.O.C.D. to witness cement operations.