

NEW MEXICO OIL CONSERVATION COMMISSION  
DRAWER DD  
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator Yates Petr. Corp.		Lease Platt"PA"		Well # 5	
Location of Well	Unit K	Section 26	Township 18	Range 26	County Eddy
Drilling Contractor	2310/S 1650/W L&M #2		Type of Equipment Rotary		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
* 9½	7"	20#		1100'	525
6¼	4½"	9.5#		3850'	375

Casing Data:

Surface \_\_\_\_\_ joints of 7" inch 20 # Grade K-SS  
(Approved) (Rejected)

Inspected by M.S. \_\_\_\_\_ date 9/22/81

Cementing Program

Size of hole 9 7/8" Size of Casing 7" Sacks cement required \_\_\_\_\_

Type of Shoe used guide Float collar used insert Btm 3 jts welded yes

TD of hole 910' Set 910' Feet of 7" Inch 20 # Grade K-SS

(New) used csg. @ 910' with 150 3%cc sacks neat cement around shoe

+ 400 sax 65/35 for additives 3%cc

Plug down @ 2:30 (AM) (PM) Date 9/23/81

Cement circulated Yes No. of Sacks 45

Cemented by Halliburton Witnessed by Mike Stillfield

Temp. Survey ran @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_ top cement @ \_\_\_\_\_

Casing test @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method Used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Checked for shut off @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Remarks: \_\_\_\_\_

No centralizers

last dip break 805'  
Drilling oil sand 920'-30'?