

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 30 through 34 shall be reported for each zone. The form is to be filed in quadruplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy	T. Lwr Canyon Lime	7234	T. Ojo Alamo	T. Penn. "B"
T. Salt	T. Strawn	7723	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka	8061	T. Pictured Cliffs	T. Penn. "D"
T. Yates	T. Miss		T. Cliff House	T. Leadville
T. 7 Rivers	T. Devonian		T. Menefee	T. Madison
T. Queen	T. Silurian		T. Point Lookout	T. Elbert
T. Grayburg	T. Montoya		T. Mancos	T. McCracken
T. San Andres	T. Simpson		T. Gallup	T. Ignacio Qtzite
T. Glorieta	T. McKee		Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger		T. Dakota	
T. Blinberry	T. Gr. Wash		T. Morrison	
T. Tubb	T. Granite		T. Todillo	
T. Drinkard	T. Delaware Sand		T. Entrada	
T. Abe	T. Bone Springs		T. Wingate	
T. Wolfcamp Ls	T. Morrow Clastics	8276	T. Chinle	
T. Penn.	T. Chester	8422	T. Permian	
T. Cisco (Bough C)	T. Miss. Lime	8549	T. Penn. "A"	

OIL OR GAS SANDS OR ZONES

No. 1, from	to	No. 4, from	to
No. 2, from	to	No. 5, from	to
No. 3, from	to	No. 6, from	to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from	to	feet
No. 2, from	to	feet
No. 3, from	to	feet
No. 4, from	to	feet

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	948	948	Surface, Rock, Redbeds	6020	6080	60	Shale, Sand, Lime
948	1043	95	Anhydrite	6080	6480	400	Lime, Shale
1043	2750	1707	Dolomite	6480	6680	200	Sand, Lime, Shale
2750	2880	130	Dolomite, Shale, Anhy.	6680	8080	1400	Lime, Shale, Sand
2880	3000	120	Dolomite, Shale	8080	8750	670	Shale, Lime
3000	3030	30	Anhydrite, Dolomite				
3030	3190	160	Dolomite				
3190	3340	150	Dolomite, Shale				
3340	3460	120	Dolomite, Sand, Shale, Anhy				
3460	3620	160	Dolomite				
3620	3780	160	Dolo, Anhy, Granite Wash				
3780	5048	1268	Dolo, Shale, Anhydrite				
5048	5200	152	Dolomite, Lime, Shale				
5200	5330	130	Lime, Shale, Anhydrite				
5330	5540	210	Anhy, Lime, Shale, Gr. Wash				
5540	6020	480	Shale, Lime				