Form 9-331 (May 1963)	DEPAR	UNITED STATES DEPARTMENT OF THE INTERIOR verse side and the structure of re- GEOLOGICAL SURVEY		Form approved. Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND SERIAL NO.			
, <u></u> , <u>_</u> , <u></u>	SUNDRY N o not use this form for pu Use "APP	NM 28864 6. IF INDIAN, ALLOTTEE OR TRIBE NAME					
1. OIL WELL	GAS WELL X OTHE	7. UNIT AGREEMENT NAME					
2. NAME OF OPERATOR Yates Petroleum Corporation /				8. FARM OR LEASE NAME Maddox QU Federal			
3. ADDRESS OF OPERATOR			·····	9. WELL NO.			
2	207 South 4th St., Artesia, NM 88210				1		
4. LOCATIO	on of WELL (Report locati o space 17 below.)	10 FIELD AND POOL, OR WILDCAT					
	990' FSL &	11. SEC., T., R., M., OR BLE. AND SURVEY OR AREA					
				Unit N, Sec. 33-18S-24E			
14. PERMIT	NO.	15. ELEVATIONS (Show whether	, , , ,	12. COUNTY OR PARISH 13. STATE			
		3716' G	R	Eddy	NM		
16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data							
	NOTICE OF 1.	NTENTION TO :	SUBSEQUENT REPORT OF:				
TEST '	WATER SHUT-OFF	PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING W	ELL		
FRACT	URE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CA	SING		
SHOOT	OR ACIDIZE	ABANDON*	SHOOTING OR ACIDIZING X	ABANDONMEN	T*		
REPAIR	RWELL	CHANGE PLANS		Casing, Perforate X			
(Other) (Nore: I Completi			(NOTE: Report results Completion or Recompl	t results of multiple completion on Well Recompletion Report and Log form.)			
prop	BE PROPOSED OR COMPLETEL osed work. If well is dir to this work.) *	OPPERATIONS (Clearly state all pertin rectionally drilled, give subsurface lo	ent details, and give pertinent dates, cations and measured and true vertice	including estimated date al depths for all markers	of starting any and zones perti-		

<u>10 8900</u>'.Ran 214 joints of 4-1/2" 11.6# and 10.5# K-55 casing as follows: 57 joints of 4-1/2" 11.6# K-55; 127 joints of 4-1/2" 10.5# K-55; 30 joints 4-1/2" 11.6# K-55; (Total 8898') of casing set at 8900'. 1-Regular guide shoe at 8900'. Flapper float set at 8858'. Cemented w/250 gallons mud flush ahead of 800 sacks 50/50 Poz, 3# KCL, 3% gel, .5% Halad 9, .3% CFR-2. Tailed in w/100 sacks Class "H". PD 6:32 AM 12-10-81. Bumped plug to 1200 psi with 2% KCL water.

WIH and perforated 8539-48' with 10 .40" holes. Ran packer and set at 8525'. Swabbed well dry. Acidized well w/2000 gallons 7-1/2% MS acid and N2 plus 5 ball sealers. Swabbed well. Show of gas.

an a	a Strategy

18. I hereby certify that the toregoing is the and correct ACCEPTED FOR RECORD and correct SIGNED/// ROGERACHAPMAD/COL	TITLE .	Engineering Secretary	DATE	1-5-82
(The space for Federal or State office use) APPROVED BY JAN 7 1981 CONDITIONS OF APPROVAL, IF ANY :	TITLE _		DATE	
U.S. GEOLOGICAL SURVEY ROSWELL, NEW MEXICO	ee Instruc	tions on Reverse Side		