

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Drawer DD  
Artesia, NM 88210

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other

JUL 1 1982

2. NAME OF OPERATOR

Yates Petroleum Corporation O. C. D. ARTESIA OFFICE

3. ADDRESS OF OPERATOR

207 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

990 FSL & 1980 FWL

AT SURFACE:

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other)

5. LEASE  
NM 28864  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Maddox QU Federal

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Und. Morrow

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Unit N, Sec. 33-T18S-R24E

12. COUNTY OR PARISH 13. STATE

Eddy NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3716' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Pulled tubing and packer. WIH and perforated 8430-8509 w/13 .50" holes. Acidized perfs in 2 stages with 7½% MS acid and ball sealers. Stage 1: 8482-8509' w/1500 gallons; Stage 2: 8430-62' w/2000 gallons. Sand frac'd perforations w/60000# sand (50000# 100 mesh sand & 55000# 20/40 sand), 20000 gallons 3% gelled acid and 3 loads CO2. Well stabilized at 180 psi on 1/4" choke = 280 mcfpd. Packer set at 8401'. RBP set at 8525'.

RECEIVED  
JUN 17 1982  
OIL & GAS  
U.S. GEOLOGICAL SURVEY Ft.  
ROSWELL, NEW MEXICO  
Set @

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Engineering Secty DATE 4-23-82

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

ACCEPTED FOR RECORD

JUN 30 1982  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO