

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	2
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	1
LAND OFFICE	1
OPERATOR	1

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

DEC 16 1981

O. C. D.
ARTESIA, OFFICE

Form C-103
Revised 10-1-75

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>		5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
Name of Operator Hondo Oil and Gas Co.		5. State Oil & Gas Lease No. 647
Address of Operator P. O. Box 1710, Hobbs, N M 88241-1710		7. Unit Agreement Name
Location of well UNIT LETTER H 1980 FEET FROM THE North LINE AND 660 FEET FROM THE East LINE, SECTION 27 TOWNSHIP 18S RANGE 28E NMPM.		8. Farm or Lease Name State BW
15. Elevation (Show whether DF, RT, GR, etc.) 3549.4' GR		9. Well No. 1
12. County Eddy		10. Field and Pool, or Wildcat Undesignated North Turkey Track Morrow

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> FULL OR ALTER CASING <input type="checkbox"/> OTHER <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/> CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/> Surface OTHER <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/> PLUG AND ABANDONMENT <input type="checkbox"/>
---	--	---	---

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drld 26" hole to 30'. Set 20" OD conductor pipe @ 30' & cmt'd w/4 yds Redi-mix to surf. Spudded 17½" hole @ 12:00 PM, 12/04/81. Finished drlg 17½" hole to 405' @ 1:30 AM, 12/05/81. FIH w/ 13-3/8" OD 54.5# K-55 set @ 405'. Cmt'd w/500 sx Cl C cmt cont'g 2% CaCl₂ & ¼#/sk celloflake. PD @ 7:00 AM, 12/05/81. Circ 150 sx cmt to pit. Cmt'd circ to surf. WOC 30 hrs. Press tstd csg to 1000# for 30 mins, OK. Drlg new fm @ 1:30 PM, 12/06/81

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED James D. Schmidt TITLE Dist. Drlg. Supt. DATE 12/09/81

APPROVED BY Mike Williams TITLE OIL AND GAS INSPECTOR DATE DEC 18 1981

CONDITIONS OF APPROVAL, IF ANY: