

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION  
P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

RECEIVED

JAN 4 1982

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

O. C. D. State ☒ For ☐  
ARTESIA, OFFICE  
5. State Oil & Gas Lease No.  
647

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL <input type="checkbox"/>	GAS WELL <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>	7. Unit Agreement Name
Name of Operator Hondo Oil and Gas Co. /			8. Farm or Lease Name State BW
Address of Operator P. O. Box 1710, Hobbs, N. M. 88241-1710			9. Well No. 1
Location of Well UNIT LETTER H 1980 FEET FROM THE North LINE AND 660 FEET FROM East LINE, SECTION 27 TOWNSHIP 18S RANGE 28E NMPM.			10. Field and Pool, or Wildcat Undersignated North Turkey Track Morrow
15. Elevation (Show whether DF, RT, GR, etc.) 3549.4' GR			12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/> Intermediate	

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Fin drlg 11" hole to 2684' @ 8:00 AM, 12/13/81. RIH w/8-5/8" OD 28# S-80 csg set @ 2684'.  
Cmtd 8-5/8" OD csg w/1500 sx BJ Lite contg 8#/sk salt, 5#/sk Gilsonite, 1/4#/sk Flocele followed  
by 200 sx C1 C cmt contg 2% CaCl<sub>2</sub>. Circ 150 sx cmt to pit. WOC 44 hrs. Press tested csg to  
1500# for 30 mins, OK.

NOTE: 8-5/8" OD csg setting depth changed from 3400' to 2800' per conversation between  
ARCO's Mr. J. Schmidt and Mr. W. A. Gressett, OCD, Artesia.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED James J. Schmidt TITLE Dist. Drlg. Supt. DATE 12/23/81

APPROVED BY Mike Williams TITLE OIL AND GAS INSPECTOR DATE JAN 5 1982

CONDITIONS OF APPROVAL, IF ANY: