

DEVON ENERGY CORPORATION
Interoffice Correspondence

9/27/2001 9:02 AM

TO: Brad Foster

FROM: W.M. Frank

RE: Add pay and stimulate
State BW Com. #1
1,980' FNL & 660' FEL
Section 27-T18S-R28E
Eddy County, New Mexico

Well Data: Elevation – 3,549' R.K.B. 3,528' GL

TD - 11,164' PBTD (CIBP) - 10,885'

Casing - 13-3/8" 54.5# K-55 @ 405' Cmt to Surface
8-5/8" 28# S-80 @ 2,684' Cmt to surface
5-1/2" 17#, L-80 @ 11,116' w/700 sx.
DV @ 7,477' cmt'd w/1,050 sxs.

2 3/8", 4.7#, N-80, 8rd Tubing
Capacity - 0.0039 Bpf Displacement - 0.00171 Bpf
Burst - 11200 psig new, 8960 psig @ 80%

Procedure

1. Locate and test Deadmen.
2. MIRU DDPU.
3. MIRU pump truck and test annulus to 1,000 psig for 15 minutes. Inform OKC if test fails. If annulus tests OK then load tubing with 35 bbls 2% KCl substitute water containing 1 gpt flowback 30 and 1 gpt corrosion inhibitor.
4. ND Tree and NU BOPE.
5. Release packer and POOH standing back tubing.