

Submit 3 Copies To Appropriate District Office

District I

1625 N. French Dr., Hobbs, NM 87240

District II

811 South First, Artesia, NM 87210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico

Energy, Minerals and Natural Resources

Form C-103

Revised March 25, 1999

OIL CONSERVATION DIVISION

2040 South Pacheco

Santa Fe, NM 87505

WELL API NO.

30-015-23996

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

K-647

7. Lease Name or Unit Agreement Name

State "BW" Com

8. Well No. 1

9. Pool name or Wildcat

Turkey Track, North (Morow)

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other

2. Name of Operator Devon Energy Production Co., L P

3. Address of Operator 20 N. Broadway, Suite 1500, Oklahoma City, OK 73102-8260

4. Well Location

Unit Letter A 1980 feet from the North line and 660 feet from the East line

Section 27 Township 18S Range 28E NMPM County Eddy

10. Elevation (Show whether DR, RKB, RT, GR, etc.)
GR=3,528' RKB=3,549'

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOBS ☐

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work). SEE RULE 1103. For Multiple Completions: Attach diagram of proposed completion or recompletion.

Devon Proposes To Plug And Abandon As Follows:

1. Cap CIBP at 10,133' with 35' cement.
2. Circulate wellbore full with 9.5ppg mud.
3. Pump balanced cement plug 9,550'- 9,650'.
4. Pump cement plug at 7,525' with 25 sxs.
5. Pump cement plug at 5,100' with 25 sxs.
6. Pump balanced cement plug 2,635'- 2,735'. WOC. Tag plug. (Intermediate casing shoe at 2,684')
7. Pump balanced cement plug 350'- 650'. WOC. Tag plug. (Surface casing shoe at 405' and salt section at 500'- 600')
8. Spot cement plug 0'-60' (also: cement to be spotted in 8 5/8" - 5 1/2" annulus).
9. Cut off casing strings 3' below surface and weld on dry hole marker.
10. Clean up and restore location.

Split Plugs 700'-800'
355'-465' (shoe plug) Tag

Note: Cement will be Class "C" at 14.8ppg with a yield of 1.32 cu ft/sx.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Charles H. Carleton TITLE Senior Engineering Technician DATE 09/09/2002

Type or print name Charles H. Carleton Telephone No. (405)552-4528

(This space for State use)
APPROVED BY Gerry Guye TITLE Compliance Officer DATE 10-3-02

Conditions of approval, if any: