Yates Petroleum Corporation Y., Turkey Track "MU" Federal #2 1980' FNL and 660' FWL Section 3% - T188 - R29E Eddy County, New Mexico

In conjunction with Form 9-331C, Application for permit to Drill subject well Yates Petroleum Corporation submits the following ten items of pertinent information in accordance with USGS requirements:

- 1. The geologic surface formation is sandy alluvium.
- 2. The estimated tops of geologic markers are as tollows:

Yates	1117'	Atoka	105461
San Andres	28951	Marrow C	lastics 11147"
Bone Springs	6968 '	Chester	Shale 11402'
Wolfcamp	87701	(PD) 11	425'
Cisco	9780'	Υ.	
Canyon	10030'		
Strawn	10246'		

3. The estimated depths at which anticipated water, oil or gas formations are expected to be encountered:

Water:	Approximately	200-240'
--------	---------------	----------

Oil or Gas:	S.A.	3000'-3060'	Atoka	10,560'-10,650'
	Wolfcamp	8690'-9000'	Morrow	1,160'-11,350'

- 4. Proposed casing program: See Form 9-331C.
- 5. Pressure control equipment: See Form 9-331C and Exhibit B.
- 6. Mud program: See Form 9-331C.
- 7. Auxiliary equipment: Kelly Cock; pit level indicators and flow sensor equipment; sub with full-opening valve on floor, drill pipe connection.
- 8. Testing, loggins and coring program: Samples: 10' spes from surface to TD DST's: As warranted, possible Cisco, Atoka, Morrow Logging: CNL-FDC T.D. to casing with GR-CNL on to surface and DLL from TD to easing with selected min. R_gO.
- 9. No abnormal pressures or temperatures are anticipated.
- 10. Anticipated starting date: As soon as possible after approval.