

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Form Approved.  
Budget Bureau No. 42-R1424

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐  
well well

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 South 4th St, Artesia, NM 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 1980' FNL & 660' FWL

AT SURFACE:

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) ☐

SUBSEQUENT REPORT OF:

☒

☐

☐

☐

☐

☐

☐

☐

☐

**RECEIVED**  
DEC 23 1981

OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

5. LEASE

NM 02058

6. IF INDIAN, ALLOTTEE OR TRIBES NAME

7. UNIT AGREEMENT NAME

O. C. D.

8. FARM OR LEASE NAME

ARTESIA, OFFICE

North Turkey Track MU Federal Com

9. WELL NO.

2

10. FIELD OR WILDCAT NAME

Ugdes. Morrow  
North Turkey Track

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Unit E, Sec. 34-T18S-R29E

12. COUNTY OR PARISH 13. STATE

Eddy

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3239.6' GR

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded a 17-1/2" hole at 7:00 PM 12-15-81.

Ran 11 joints 13-3/8" 48# K-55 casing set at 445'. Cemented w/500 sacks Class C 2% CaCl. Cement circulated 40 sacks to pit. PD 12:00 AM 12-16-81. Bumped plug to 1500 psi, released pressure and float held okay. WOC. Drilled out 1:00 PM 12-16-81. WOC 31 hours. Reduced hole to 12-1/4". Drilled plug and resumed drilling.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Engineering Secty DATE 12-21-81

APPROVED BY  
CONDITIONS OF

ACCEPTED FOR RECORD

PETER W. CHESTER

DEC 28 1981

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

Space for Federal or State office use

TITLE

DATE

See Instructions on Reverse Side