

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

NM OIL CONS. COMMI.  
SUBMIT IN TRIPPLICATE  
Draw on other instructions on re-  
verse side  
Artesia, NM 88210

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 02056

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

North Turkey Track MU Fed. Co.

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

North Turkey Track  
Sec. Morrow

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Unit E, Sec. 34-T18S-R29E

12. COUNTY OR PARISH 13. STATE

Eddy

NM

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Yates Petroleum Corporation

JAN 8 1982

3. ADDRESS OF OPERATOR

207 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State Regulations. See also space 17 below.)

At surface

1980' FNL & 660' FWL, Sec. 34-18S-29E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3239.6' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Ran 74 joints of 8-5/8" casing as follows: 20 joints of 8-5/8" 32#; 54 joints of 8-5/8" 24# (Total 3003') of casing set at 3000'. 1-Texas Pattern guide shoe at 3000'. Flapper float at 2960' Cemented w/1550 sacks 65/35 Poz & 200 sacks Class "C" 2% CaCl<sub>2</sub>. PD 8:30 PM 12-22-81. Bumped plug to 1000 psi, released pressure & float held, okay. Had full returns but cement did not circulate. WOC 6 hours. Ran Temperature Survey & found top of cement at 510'. Spotted 200 sacks Class "C". PD 4:30 AM 12-23-81. Circulated 35 sacks to pit. WOC. Drilled out 9:00 AM 12-26-81. WOC 84 hours & 30 minutes. Nippled up & tested to 1000 psi, okay. Reduced hole to 7-7/8". Drilled plug & resumed drilling.

RECEIVED  
JAN - 6 1982

OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED ROGER A. CHAPMAN

TITLE Engineering Secretary

DATE 1-5-82

(This space for Federal or State office use)

APPROVED BY JAN 7 1981  
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

\*See Instructions on Reverse Side