Artesia, NM 88210

RECEIVED

Form 9-331 Form Approved. Dec. 1973 Budget Bureau No <del>11</del>2 1982 UNITED STATES 5. LEASE DEPARTMENT OF THE INTERIOR FED. LC 055696 6. IF INDIAN, ALLOTTEE OR TRIBE NAME C. D. **GEOLOGICAL SURVEY** SF ARTESIA. OFFICE 7. UNIT AGREEMENT NAME SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331–C for such proposals.) 8. FARM OR LEASE NAME YATES PREMIER FEDERAL # 1 gas well XXX well other 9. WELL NO. 2. NAME OF OPERATOR PREMIER PRODUCTION COMPANY 10. FIELD OR WILDCAT NAME 3. ADDRESS OF OPERATOR UNDES. SAN ANDRES 324 W. Main Artesia New Mexico 88210 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 SEC 22 T 18 S R 29 E AT SURFACE: 1980' FEL 660' FSL 12. COUNTY OR PARISH 13. STATE AT TOP PROD. INTERVAL: Eddy New Mexico AT TOTAL DEPTH: 14. API NO. 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT. OR OTHER DATA 15. ELEVATIONS (SHOW DF, KDB, AND WD) 3466 SUBSEQUENT REPORT OF: REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT XX SHOOT OR ACIDIZE REPAIR WELL (NOTE: Regord results of multiple completion or zone PULL OR ALTER CASING nge on Form 9-330.) 1982 MULTIPLE COMPLETE CHANGE ZONES ABANDON\* Oil & GAS

ROSWELL NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

U.S. GEOLOGICAL SURVEY

1-29-82; SET PACKER & RBP & FRAC'D Thru Perfs. 2774'-91'. 10 Perfs W/ 20000 Gal. Gel& 2% KCL Water & 16,000 # 20-40 Sand & 5500 # 10-20 Sand. SHUT IN 2 HRS. & Flo'D Back 40 BBLS Water.

(other)

SET PACKER & RBP TO FRAC THRU PERFS. 2534'-43'. 10Perfs. W/20,000 Gal Gel/2% KCL Water & 16,000 # 20-40 sand & 5500 # 10-20 Sand. Shut in 6 Hrs. & Flo'd Back 50 BBLS overnit

1-30-82; SET PACKER & RBP & FRAC'D Thru Perfs. 2080'-91'. 10 Perfs. W/21,000 GA1 Ge1/2% Kcl Water & 18,500 # 20-40 Sand& 7000# 10-20 Sand. Shut in 24HRS. Flo'd back 20Ga1. Min.

Subsurface Safety Valve: Manu. and Type		Set @ Ft.
18. I hereby certify that the foregoing is tr	V 401	0 // ~
YAR CEPTED/FOX RECORD//	MITLE DEW	DATE 21682
ROGER Á. CHAPMAN	(This space for Federal or State office use)	
CONDITIONS OF TEROZA 8 1982	TITLE	DATE
U.S. GEOLOGICAL SURVEY	*See Instructions on Reverse Side	